




Architectural Linear						Downlighting		
Litecontrol						Kurt Versen	Prescolite	
Aira	MODx	Note (67L)	NELO™ (70L, 75L)	Stance	SAE101	Noni™	LITEISTRY™	LiteFrame® 2.0

Recessed							Strip	Surface Mount
Litecontrol	Columbia Lighting					Lifeshield	Columbia Lighting	Columbia Lighting
Ryvi (55L)	Versify™ (VSY)	Transition® (NBT)	LCAT	LCAT-S	TCAT	Kloven (KLO)	MPS	Escalate™ (ESL)

Wall Mount				High & Low Bay Lighting			
Columbia Lighting		Lifeshield		Columbia Lighting			
CWM	Revalume™ (RLW)	Wall 3 (W3B)	Prevent (PVNT)	Echelân (ECH)	PELA	Utilibay™ (UTB2)	Reverie™ (RLB)

	Control Option Ordering Logic & Description	Control Option Functionality							Control Option Components
		Networkable	Grouping	Scheduling	Occupancy / Motion	Daylight Harvesting	0-10V Dimming	On/Off Control	
NX Wireless									
NX Connect									
NX Wired									
Independent									

The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Current is under license. Other trademarks and trade names are those of their respective owners.

Current  **currentlighting.com**

© 2025 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

Page 1 of 1
Rev 06/25/25
NX_Indoor Luminaire Look-up Guide_R04