

Sustainability | Our Future

Dual-Lite's sustainability mission, "To achieve an ongoing culture of environmental responsibility with our employees, community, and industry by implementing educational programs and sustainable practices." and vision serve as a foundation for our new product development efforts. Dual-Lite's vision for this initiative is to be recognized as a leader in conservation efforts to sustain our natural resources and protect our environment.

Part of this vision is to utilize new technology to reduce the materials and energy required to manufacture, pack, ship and maintain newly designed products. The EV is the next step in Dual-Lite's product development to support and promote this vision by including the following sustainable practices:

- Reduced plastic content plastic content has been reduced by 50% which has resulted in smaller packaging and reduced transportation impact
- Reduced power requirements The use of cutting edge LED technologies allows for less power requirements for battery charging
- Minimizing maintenance requirements The LEDs utilized by the EV unit have a Lifetime Warranty, no lamps to be changed meaning less materials sent to our landfills
- The use of "Green" batteries Using Nickel Metal Hydride (NiMH) batteries over Lead Acid and Nickel Cadmium batteries reduces harmful chemicals and hazardous cadmium waste from landfills and water sources







Value | A Class of its Own

Now that you have seen what the EV has to offer in terms of product capabilities, we saved the best part for last - VALUE. A product's value is the culmination of benefits it provides when compared to its total cost. The EV emergency light provides:

For the Owner:

• Energy savings, extended product warrantees, reduced maintenance costs, and easy disposal

For the Installer:

• Simplified installation and great performance from a trusted brand

For the Designer:

• Low profile, unobtrusive design with optical and electrical performance that surpasses NFPA code requirements

For the Distributor:

• Pricing on par with traditional emergency lighting products and a reduced shelf-space footprint



Dual-Lite first incorporated high brightness white LEDs in the PG Series followed by its UL924 MR16 LED lamp and now in the most technologically advanced emergency light on the market the EV Series. "The Evolution of Emergency Lighting" has begun and Dual-Lite, the first name in emergency lighting, is leading the way.

Current 🗐

Current Lighting Solutions, LLC 701 Millennium Blvd. Greenville, SC 29607

currentlighting.com/dual-lite

© 2022 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.

Rev 05/24/22 0603501a_ev_counter_disp_pamphlet_R01





PERFORMANCE DESIGN AESTHETICS VALUE SUSTAINABILITY

The "Evolution" of Emergency Lighting...

0603501A 1/2013 Current ⁽²⁾





Patent Pending

"The Evolution of Emergency Lighting" has begun with the most technologically advanced emergency light on the market.

The tangible benefits of the EV Series are founded in the following characteristics: **Aesthetics**, **Design**, **Performance**, **Sustainability** and **Value**.



Aesthetics | Sleek architectural styling

Break-throughs in LED technology, increased energy-density batteries, and surface mount electronics have resulted in circuits and optics which are greatly reduced in size and require much less energy while providing increased amounts of light. These characteristics all contribute to a much smaller and more powerful emergency light. The EV packs these characteristics into a small housing with the following features.

• INCONSPICUOUS

• COMPACT

• ARCHITECTURAL

• SLEEK



Design | Ease of Installation and Maintenance

Dual-Lite focused on ease of installation, maintenance, and longevity of service when designing the EV emergency lighting unit. The unique LED light engine and thermal management design are paired with beneficial options like polarity sensing circuitry and redundant LED operation. Redundant LED operation ensures the unit will continue to operate at reduced light output in the event one of the LEDs fails. The EV also uses an environmentally friendly battery source as opposed to the traditional lead acid or Nickel Cadmium based batteries which contain elements that when disposed of improperly are harmful to the environment.

ADDITIONAL DESIGN FEATURES:

- 50% less plastic than traditional units
- Long life-cycle LEDs rated at 100,000 hours
- RoHS Compliant
- Wall or ceiling mount
- Intelligent 120 or 277 VAC input wiring



erformance | Sophisticated LED based lamp-head

While most contemporary emergency lights use a minimum of 10 watts to light a given space, the EV Series offers superior spacing of up to 27' while requiring only 2 watts to power. The EV uses a high energy density Nickel Metal Hydride(NiMH). This battery technology is used extensively in hybrid automobiles and other applications due to their high energy density. The use of NiMH batteries combined with the low wattage required to power the LEDs allows for a reduced amount of input power required to maintain a full battery charge while providing a superior performing emergency lighting unit.

ADDITIONAL PERFORMANCE FEATURES

- The LEDs are mounted inside a die-cast housing which utilizes precision components to offer adjustability and thermal stability
- Superior light output with optimized spacing and uniform bright LED light with no irregular light patterns or hot-spots
- Optional Spectron® self-test/self-diagnostics offers user initiated testing for 1 or 90 minutes by pushing a test switch and automatic testing on a monthly basis
- The EV unit with remote capacity will also run a 2 headed remote (EV2R) to double overall coverage and offer initial product savings.

Multi-Unit Spacing





Single Unit Coverage



Meets Life Safety Code minimum illuminance of 0.1 fc and average illuminance of 1.0 fc. Assumes open space with no obstructions, mounting height of 7.5', ceiling height of 9' and reflectances of 80/50/20.