








FLOODLIGHTS

PRODUCT SELECTION GUIDE

| | | GOOD | | | | | | BETTER | | | | | | BEST | | | | | |
|-------------|---|---|--------|------|---|--------|----------|--|--------|----------|---|--------|-----------------------------------|---|--------|--------------------|---|--------|------|
| | | tradeSELECT [™] | | | tradeSELECT [™] | | | tradeSELECT [™] | | | tradeSELECT [™] | | | | | | | | |
| | |  | | |  | | |  | | |  | | |  | | |  | | |
| | | Colt Mini | | | Marshal | | | Colt LBUL | | | Lightscaper [®] | | | Sling Flood | | | Ratio Flood | | |
| FEATURES | Easy to Install | Yes | | | | | | Yes | | | | | | Yes | | | | | |
| | Mounting Options | ½" 14 NPS | | | Junction box | | | ½" 14 NPS | | | ½" 14 NPS | | | Threaded Knuckle, Slipfitter & Trunnion | | | Threaded Knuckle, Slipfitter & Trunnion | | |
| | Features | + | | | + | | | ++ | | | ++ | | | ++ | | | +++ | | |
| | Maintenance | Low, Aiming | | | Low, Aiming | | | Low, Aiming | | | Med, Aiming, Adjustment | | | Low, Aiming | | | Low, Aiming | | |
| PERFORMANCE | Lumens | 1115 | | | 2104 | | | 2000 | | | 984-2009 | | | 2,500-40,000 | | | 3500-30,000 | | |
| | Watts | 13W | | | 20W | | | 21W | | | 8W, 16W | | | 20-320W | | | 25-265W | | |
| | Efficacy (maximum LPW) | 85 | | | 100 | | | 89-94 | | | 116-128 | | | 122-128 | | | 140 | | |
| | Distribution | NEMA 6X6 Wide | | | NEMA 6X6 Wide | | | NEMA 6X6 Wide | | | NEMA 7X6 Wide | | | 7x7 Wide | | | Narrow, Medium, Wide | | |
| | CCT | 3000K | | | 3000K | | | 4000K | | | 3000K/4000K/5000K | | | 4000K | | | 3000K, 4000K, 5000K | | |
| | CRI | 70 | | | 80 | | | 70 | | | 70-100 | | | 70 | | | 70 | | |
| | Certifications | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 |
| | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Product Life | 60,000hrs. | | | 60,000hrs. | | | >60,000 hrs. | | | 60,000hrs. | | | >60,000 hours | | | >60,000hrs. | | |
| | HID Equivalence | 70W | | | 100W | | | 150W | | | 100W, 120-277V | | | 100W-1,000W | | | 100W, w1000W | | |
| | Energy Savings (Based on HID Equivalence) | 86% | | | 85% | | | 83% | | | 86% | | | 76% | | | 76% | | |
| Voltage | 120V | | | 120V | | | 120-277V | | | 120-277V | | | 120V(20 & 40W), 120-277V(80-320W) | | | 120-277V, 347-480V | | | |
| CONTROLS | Basic occupancy | - | | | Yes | | | - | | | - | | | - | | | Yes | | |
| | Occupancy and Daylight Harvesting | - | | | Yes | | | - | | | - | | | - | | | Yes | | |

WALL PACKS

PRODUCT SELECTION GUIDE


| | | GOOD | | | | | BETTER | | | | | BEST | | | | | | | | | | |
|---|-----------------------------------|---|---------|----------|---|---------|----------|--|---------|----------|--|---------|----------|---|---------|----------|--|---------|--------------------|---|---------|------|
| | | tradeSELECT [®]  NRG 300L | | | tradeSELECT [®]  PRS PERIMASHIELD | | | tradeSELECT [®]  WGH | | | tradeSELECT [®]  WGH2/WGH3 | | | tradeSELECT [®]  SLING Wall | | | tradeSELECT [®]  Prelude Wallpacks | | |  Ratio Wall | | |
| FEATURES | Easy to Install | Yes | | | Yes | | | Yes | | | Yes | | | Yes | | | Yes | | | | | |
| | Mounting Options | Junction box | | | Junction box | | | Junction box | | | Junction box | | | Side Door, Junction box | | | Mounting Plate, Junction box | | | Junction box, Conduit | | |
| | Features | + | | | + | | | ++ | | | +++ | | | +++ | | | +++ | | | +++ | | |
| | Maintenance | Low | | | Low | | | Low | | | Low | | | Low | | | Low | | | Low | | |
| PERFORMANCE | Lumens | 1800 | | | 2500 | | | 2900–12,800 | | | 4600–17,200 | | | 2200–8100 | | | 2500–8600 | | | 1000–19,500 | | |
| | Watts | 17W | | | 20W | | | 32–110W | | | 30–120W | | | 21–80W | | | 18–60W | | | 10–155W | | |
| | Efficacy (maximum LPW) | 110 | | | 125 | | | 105–120 | | | 140–147 | | | 110–115 | | | 139–144 | | | 148 | | |
| | Distribution | Type IV | | | Type IV | | | Type IV | | | Type IV | | | Type IV | | | Type II (Cut Off), Type IV (Refractor) | | | Type II, Type III, Type IV | | |
| | CCT | 4000K, 5000K | | | 4000K, 5000K | | | 4000K, 5000K | | | 4000K, 4500K, 5000K | | | 3000K, 4000K, 5000K | | | 3000K, 4000K, 5000K | | | 3000K, 4000K, 5000K | | |
| | CRI | 70 | | | 70 | | | 70 | | | 70 | | | 70 | | | 70 | | | 70 | | |
| | Certifications | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 | Listed for Wet Locations | UL 1598 | IP65 |
| | | Yes | Yes | – | Yes | Yes | – | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Product Life | 60,000hrs. | | | 60,000 hrs. | | | 60,000hrs. | | | >60,000hrs. | | | >60,000hrs. | | | >60,000hrs. | | | >60,000hrs. | | |
| | HID Equivalence | 70W | | | 150W | | | 150–400W | | | 150–400W | | | 100–250W | | | 70–250W | | | 42–400W | | |
| Energy Savings (Based on HID Equivalence) | 75% | | | 77% | | | 75–80% | | | 75–80% | | | 70–80% | | | 75–80% | | | 76% | | | |
| Voltage | 120–277V | | | 120–277V | | | 120–277V | | | 120–277V | | | 120–277V | | | 120–277V | | | 120–277V, 347–480V | | | |
| CONTROLS | Basic occupancy | Yes | | | Yes | | | Yes | | | Yes | | | Yes | | | – | | | Yes | | |
| | Occupancy and Daylight Harvesting | – | | | – | | | – | | | Yes | | | Yes | | | – | | | Yes | | |

DUSK TO DAWN

PRODUCT SELECTION GUIDE

BEST

tradeSELECT™





SLING SGD

| FEATURES | Easy to Install | Yes | | | |
|-------------|---|----------------------------------|--------|------|--|
| | Mounting Options | 2 3/8"-1 5/8", Pipe & Wall Mount | | | |
| | Features | ++ | | | |
| | Maintenance | Low, Aiming | | | |
| PERFORMANCE | Lumens | 6230-8175 | | | |
| | Watts | 40-60W | | | |
| | Efficacy (maximum LPW) | 145-156 | | | |
| | Distribution | Type V | | | |
| | CCT | 4K, 45K, 5K | | | |
| | CRI | 70 | | | |
| | Certifications | Listed for Wet Locations | UL1598 | IP65 | |
| | | Yes | Yes | Yes | |
| | Product Life | 60,000hrs. | | | |
| | HID Equivalence | 100-250W | | | |
| | Energy Savings (Based on HID Equivalence) | 78% | | | |
| Voltage | 120-277V | | | | |
| CONTROLS | Basic occupancy | No | | | |
| | Occupancy and Daylight Harvesting | No | | | |

VAPORTITES




PRODUCT SELECTION GUIDE

GOOD

| | | tradeSELECT [®] | | | tradeSELECT [®] | | | |
|--------------------|--|--|--------------------------|----------|--|--------------------------|--------|------|
| | |  VGBL | | |  VWGL | | | |
| FEATURES | Easy to Install | Yes | | | Yes | | | |
| | Mounting Options | Standard J-Box-Ceiling-4 sided ½" 14 NPS threaded conduit entry | | | Standard J-Box-Ceiling-4 sided ½" 14 NPS threaded conduit entry | | | |
| | Features | ++ | | | ++ | | | |
| | Maintenance | Low | | | Low | | | |
| PERFORMANCE | Lumens | 757 | | | 757 | | | |
| | Wattage | 11W | | | 11W | | | |
| | Efficacy (maximum LPW) | 70 | | | 70 | | | |
| | CCT | 4100K | | | 4100K | | | |
| | CRI | 80 | | | 80 | | | |
| | Certifications | | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 |
| | | | Yes | Yes | Yes | Yes | Yes | Yes |
| | Product Life | 60,000hrs. | | | 60,000hrs. | | | |
| | HID Equivalence | 100w | | | 100w | | | |
| | Energy Savings (Based on HID Equivalence) | 82% | | | 82% | | | |
| Voltage | 120-277V | | | 120-277V | | | | |

CANOPY

PRODUCT SELECTION GUIDE

| | | GOOD | | | BETTER | | | BEST | | |
|----------------|-----------------------------------|---|--------|----------|--|--------|----------|--|--------|------|
| | | tradeSELECT [®]  SLING CANOPY | | | Additional Canopy  LUMASQUARE | | | Additional Canopy  BEACON DRIVE | | |
| FEATURES | Easy to Install | Yes | | | Yes | | | Yes | | |
| | Mounting Options | Standard J-Box-3/4" Pendant, 3 sided 1/2" 14 NPS threaded conduit entry | | | Standard J-Box or 3/4" Pendant | | | Standard J-Box or 3/4" Pendant | | |
| | Features | ++ | | | ++ | | | +++ | | |
| | Maintenance | Low | | | Low | | | Low | | |
| PERFORMANCE | Lumens | 3200-8000 | | | 3000-9000 | | | 2,500-16,000 | | |
| | Watts | 20-60W | | | 25-75W | | | 20-55W | | |
| | Efficacy (maximum LPW) | 134-142 | | | 120-127 | | | 109-125 | | |
| | Distribution | Type V | | | Type V | | | Type V, Type VC, Type VRW, Type IV | | |
| | CCT | 4000K | | | 3000K, 4000K, 5000K | | | 3000K, 4000K, 5000K | | |
| | CRI | 70 | | | 70 | | | 70 | | |
| | Certifications | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 | Listed for Wet Locations | UL1598 | IP65 |
| | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Product Life | >60,000hrs. | | | >60,000hrs. | | | >60,000hrs. | | |
| | HID Equivalence | 100-250W | | | 175-250W | | | 175-250W | | |
| Energy Savings | 75% | | | 75% | | | 78% | | | |
| Voltage | 120-277V | | | 120-277V | | | 120-277V | | | |
| CONTROLS | Basic occupancy | - | | | Yes | | | Yes | | |
| | Occupancy and Daylight Harvesting | - | | | Yes | | | Yes | | |
| | Integrated Controls | - | | | - | | | NX | | |