



LED Retrofit Lamps Approved for Hazardous Locations

A Smart, Safe Switch From HID

AVAILABLE ONLY IN TYPE B



RATED FOR:

**CLASS I, DIVISION 2,
GROUPS A, B, C, D**

**CLASS II, DIVISION 1,
GROUPS E, F, G**

**CLASS II, DIVISION 2,
GROUPS F, G**



**INDUSTRY-LEADING
LUMEN OUTPUT IN
COMPACT FORM**



**UL-CERTIFIED
FIXTURES***

GE Lighting Filtr-Gard® H2 Series
GE Lighting Powr-Gard® H9 Series
Crouse-Hinds Champ® VMV
Appleton Mercmaster™ II
Appleton Mercmaster™ III
Hubbell Killark® VM Series
Holophane Petrolux® P3M
Holophane Petrolux® II PETL
Thomas & Betts Hazlux® 3 Series



50,000-hour rated life
2.5x longer life than HID



50% less energy usage
with similar light output -
up to 23,500 lumens



E39 socket adapter
included with
E26 base lamps



**High maximum
temperature ratings**
21W: 65°C | 35W: 55°C
45W: 45°C | 80W: 55°C
150W: 40°C

Minimum starting
temperature: -20°C

**For use at drilling rigs, petrochemical facilities, food and beverage facilities
and other heavy-industry areas**

*Suitable luminaire fittings may vary. Contact your Current representative or check installation guide for details.