



LED Plug-in

2G11 Ballast Compatibility Guide



Current @



LED Plug-in Ballast Compatibility Guide

2G11

	Compatible		Not Applicable
	Not Compatible		Use with caution - PF<0.9 or THD>20%

IMPORTANT NOTICE: This list is based in part on information provided by the ballast supplier, and testing was done on a stable AC power supply under laboratory, which may not be representative of your particular end-use conditions. While each ballast type listed has undergone testing, some have undergone revisions that may change operating parameters and impact lamp performance. Applications and conditions of use are many and varied and beyond Current's control, so purchasers and users should make their own determinations as to the suitability of a lamp-ballast combination for their own particular application and use. Compatibility may also extend to ballasts beyond this list, so performing an on-site test before installation is recommended.

High Lumen Biax® Plug-In Ballast Compatibility

Brand	Ballast Type	Full Load		N-1	
		120V	277V	120V	277V
GE	GEC140MAX-A				
GE	GEC240MAX-A				
GE	GEC340MAX-A				
GE	GEC240MVPS-A				
GE	GEC225MVPS-A				
Philips	ICN-1TTP40-SC				
Philips	ICN-2TTP40-SC				
Philips	ICN-3TTP40-SC				
Osram	QHE 1x40DL/UNV ISN-SC				
Osram	QHE 2x40DL/UNV ISN-SC				
Osram	QHE 3x40DL/UNV ISN-SC				
Universal	C240PUNVHP-B				

Compatibility may vary per revision.
Information is subject to change without notice.