



10-Day Quick Ship Program Square Straight Steel Poles

- 1,200 combinations available
- Ships within 10 days
- Five different colors available
- 16'-30' pole lengths
- 4"-5" square
- Same high quality as standard poles


COLORS AVAILABLE



BLT Black Matte Textured



BLS Black Gloss Smooth



DBT Dark Bronze Matte Textured



PSS Platinum Silver Smooth



LGT Light Grey Gloss Smooth

10-Day Quick Ship Program Square Straight Steel Poles



ORDERING INFORMATION

Limit of 15 poles



Cross Section	Luminaire Mounting Type	Drill Pattern	Finish	Options
SSS-H-16-40-A	1 Single arm mount	S2 2 bolt, 3 1/2" Pattern	BLT Black Matte Textured	LAB Less anchor bolts & template
SSS-H-18-40-A	2 Two fixtures at 180	B3 2 bolt, 2 1/2" Pattern (Ratio)	BLS Black Gloss Smooth	VM2 2nd mode vibration damper
SSS-H-20-40-A	2L Two fixtures at 90		DBT Dark Bronze Matte Textured	
SSS-H-25-40-A	3T Three fixtures at 90		PSS Platinum Silver Smooth	
SSS-H-30-40-B	4 Four fixtures at 90		LGT Light Grey Gloss Smooth	
SSS-H-30-50-B	TA Tenon (2 3/8" OD)			
	TB Tenon (2 7/8" OD)			
	TC Tenon (3.5" OD)			
	TR Removeable tenon (2.375 x 4.25)			
	OT No drilling (includes pole cap)			

ORDERING GUIDE

Limit of 15 poles

Cross Section	Height		Nominal Shaft Dimensions	Wall Thickness	Bolt Circle Suggested	Bolt Circle Range	Bolt Square Range	Base Plate Square	Anchor Bolt Size	Bolt Projection	Pole Weight
	Feet	Meters									
SSS-H-16-40-A-XX-XX	16	4.9	4" Square	.125"	9"	8" - 10"	5.66" - 7.07"	9"	3/4" x 30" x 3"	3.5	116
SSS-H-18-40-A-XX-XX	18	5.5	4" Square	.125"	9"	8" - 10"	5.66" - 7.07"	9"	3/4" x 30" x 3"	3.5	129
SSS-H-20-40-A-XX-XX	20	6.1	4" Square	.125"	9"	8" - 10"	5.66" - 7.07"	9"	3/4" x 30" x 3"	3.5	142
SSS-H-25-40-A-XX-XX	25	7.6	4" Square	.125"	9"	8" - 10"	5.66" - 7.07"	9"	3/4" x 30" x 3"	3.5	175
SSS-H-30-40-B-XX-XX	30	9.1	4" Square	.188"	11"	10" - 12"	7.07" - 8.48"	10.5"	3/4" x 30" x 3"	3.5	304
SSS-H-30-50-B-XX-XX	30	9.1	5" Square	.188"	11"	10.25" - 13.25"	7.25" - 9.37"	11.5"	1" x 36" x 4"	4.5	387

WIND MAP/EPA

Reference Wind Map and EPA information:

[SSS-H SPECIFICATION PAGE](#)

10-DAY QUICK SHIP VIPER, RATIO AND SLING AREA/SITE

