

WALL PACKS

PRODUCT SELECTION GUIDE

		GOOD					BETTER					BEST										
		tradeSELECT [®] NRG [™] 300L			tradeSELECT [®] PRS PERIMASHIELD		tradeSELECT [®] WGH			tradeSELECT [®] WGH2/WGH3			tradeSELECT [®] SLING Wall			tradeSELECT [®] Prelude Wallpacks			Ratio Wall			
FEATURES	Easy to Install	Yes			Yes		Yes			Yes			Yes			Yes						
	Mounting Options	Junction box			Junction box		Junction box			Junction box			Side Door, Junction box			Mounting Plate, Junction box			Junction box, Conduit			
	Features	+			+		++			+++			+++			+++			+++			
	Maintenance	Low			Low		Low			Low			Low			Low			Low			
PERFORMANCE	Lumens	1800			2500		2900–12,800			4600–17,200			2200–8100			2500–8600			1000–19,500			
	Watts	17W			20W		32–110W			30–120W			21–80W			18–60W			10–155W			
	Efficacy (maximum LPW)	110			125		105–120			140–147			110–115			139–144			148			
	Distribution	Type IV			Type IV		Type IV			Type IV			Type IV			Type II (Cut Off), Type IV (Refractor)			Type II, Type III, Type IV			
	CCT	4000K, 5000K			4000K, 5000K		4000K, 5000K			4000K, 4500K, 5000K			3000K, 4000K, 5000K			3000K, 4000K, 5000K			3000K, 4000K, 5000K			
	CRI	70			70		70			70			70			70			70			
	Certifications	Listed for Wet Locations	UL 1598	IP65	Listed for Wet	UL 1598	IP65	Listed for Wet Locations	UL 1598	IP65	Listed for Wet Locations	UL 1598	IP65	Listed for Wet Locations	UL 1598	IP65	Listed for Wet Locations	UL 1598	IP65	Listed for Wet Locations	UL 1598	IP65
		Yes	Yes	–	Yes	Yes	–	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	Product Life	60,000hrs.			60,000 hrs.		60,000hrs.			>60,000hrs.			>60,000hrs.			>60,000hrs.			>60,000hrs.			
	HID Equivalence	70W			150W		150–400W			150–400W			100–250W			70–250W			42–400W			
Energy Savings (Based on HID Equivalence)	75%			77%		75–80%			75–80%			70–80%			75–80%			76%				
Voltage	120–277V			120–277V		120–277V			120–277V			120–277V			120–277V			120–277V, 347–480V				
CONTROLS	Basic occupancy	Yes			Yes		Yes			Yes			Yes			–			Yes			
	Occupancy and Daylight Harvesting	–			–		–			Yes			Yes			–			Yes			