

NOTE: Components shown in images are representative only and may vary based on the configuration ordered.

#### **IMPORTANT SAFEGUARDS**

When using electrical equipment, basic safety precautions should always be followed including the following:

- a. READ AND FOLLOW ALL SAFETY INSTRUCTIONS.
- b. Do not use outdoors.
- c. Do not mount near gas or electric heaters.
- d. Equipment should be mounted in locations and at heights where it will not readily be subjected to tampering by unauthorized personnel.
- e. The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition.
- f. Do not use this equipment for other than intended use.

#### **WARNINGS**

1. This product contains chemicals known to the state of California to cause cancer, birth defects and/or other reproductive harm. Thoroughly wash hands after installing, handling, cleaning, or otherwise touching this product.
2. Contact Current for information and direction before relamping or replacing this light fixture.
3. Disconnect power before installing or servicing. Observe all precautions usually followed when dealing with high voltage equipment when installing or servicing this light fixture.
4. The product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
5. Protect all wiring connections with approved insulators rated 600V / 150°C (by others).
6. Selected fixture voltage must match supply line voltage.

#### **SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE**

Upon receipt of this fixture, thoroughly inspect it for any damage. If any is found, the carrier should be notified and held accountable.

## **INSTALLATION INSTRUCTIONS**

### **STEP 1**

Disconnect electrical power and remove dock light that is to be replaced, if applicable.

### **STEP 2**

Select a location and drill four holes using the drill template included. Be sure to select the proper hole pattern for the model being installed.

### **STEP 3**

For solid surfaces; 3/8 inch lag bolts with appropriate expansion anchors are recommended. For hollow wall with rear access, use 3/8 inch bolts, washers, lock washers and nuts.

### **STEP 4**

Secure LED dock light assembly to the end of the lamp arm. Dock light shall be secured to the dock arm assembly with the use of washers, lock washers and nuts via the mounting yoke of the fixture.

### **STEP 5**

Adjust mounting angle of the unit.

### **STEP 6**

Make all necessary wiring connections, reconnect electrical power.