


## Sensor Selection Tool

Current provides intuitive and flexible deployment options to meet code, enhance comfort, increase energy savings and improve operating efficiency.

### OMNI DT PIR US



### LIGHTOWL DT PIR US



### LIGHTHAWK DUAL TECH PASSIVE INFRARED ULTRASONIC



### LIGHTHAWK ULTRASONIC



### LIGHTHAWK PASSIVE INFRARED



### BLUETOOTH WASP



### DIMMING WASP



### WASP



APPLICATIONS	OMNI® Dual Tech Passive Infrared/Ultrasonic		OMNI Ultrasonic		OMNI Passive Infrared	LightOWL® Dual Tech Passive Infrared/Ultrasonic	LightOWL Passive Infrared	Dimming LightHAWK® Dual Tech Passive Infrared/Ultrasonic	Dimming LightHAWK Passive Infrared	LightHAWK Dual Tech Passive Infrared/Ultrasonic				LightHAWK Ultrasonic	LightHAWK Passive Infrared				Bluetooth WASP™				Dimming WASP				WASP							
	OMNIDT2000	OMNIDT500	OMNIUS2000	OMNIUS500	OMNIIRL	LODT	LOIRWVRP	LOIRHBRP	LHRDMMTS2	LHRDMIRS3	LHRMST1	LHRMST50	LHRDCMTD2	LHRDCMTD0	LHRUSS1	LHRUSS0	LHRIRS1	LHRIRS0	LHRDCIRD2	LHL-IRS1	WSPDBEM	WSPDLWOBEM	WSPDBSM	WSPDLWOSM	WSPDEM	WSPDLWOEM	WSPDSM	WSPDLWOSM	WSPDEM	WSPDLWOEM	WSPDSM	WSPDLWOSM		
Break Rooms		•			•	•				•	•	•	•																					
Cleanrooms					•																													
Cafeterias	•	•			•	•	•			•	•	•	•																					
Classrooms - Small		•				•				•	•	•	•																					
Classrooms - Large	•					•				•	•	•	•																					
Closets		•			•																													
Conference Halls	•					•																												
Conference Rooms	•	•				•				•	•	•	•																					
Hallways			•																															
Kitchens			•	•			•																											
Labs	•				•	•	•																											
Libraries	•		•	•		•				•	•	•	•																					
Meeting Rooms		•				•				•	•	•	•																					
Open Offices	•					•				•	•	•	•																					
Private Offices		•				•				•	•	•	•																					
Restrooms			•	•											•	•																		
Show Floors	•																																	
Stairways			•																															
Storage Facilities		•			•	•	•			•	•	•	•																					
Training Rooms	•	•				•				•	•	•	•																					
Garages																						•	•	•	•	•	•	•	•	•	•	•	•	•
Gymnasiums																						•	•	•	•	•	•	•	•	•	•	•	•	•
Cold Storage																						•	•	•	•	•	•	•	•	•	•	•	•	•
Parking Lots																						•	•	•	•	•	•	•	•	•	•	•	•	•
Manufacturing Floors																						•	•	•	•	•	•	•	•	•	•	•	•	•
Site/Area																						•	•	•	•	•	•	•	•	•	•	•	•	•
Warehouses																						•	•	•	•	•	•	•	•	•	•	•	•	•
SPECIFICATIONS																																		
IntelliDAPT®	Yes		Yes		Yes	Yes	Yes	Yes	Yes	Yes				Yes	Yes				No	No				No				No						
Bluetooth®	No		No		No	No	No	No	No	No				No	No				Yes	Yes				No				No						
Manual Override	Yes (with UVPPM/UVPPHD and Low Voltage Switch)		Yes (with UVPPM/UVPPHD and Low Voltage Switch)		Yes (with UVPPM/UVPPHD and Low Voltage Switch)	Yes (with UVPPM/UVPPHD and Low Voltage Switch)	Yes (with UVPPM/UVPPHD and Low Voltage Switch)	Yes	Yes	Yes	No	Yes	No	Yes	No	Yes	No	Yes	Yes	Yes	Yes				No									
Coverage	2000 sq. ft	500 sq. ft	2000 sq. ft	500 sq. ft	1500 sq. ft	1600 sq. ft	1600 sq. ft	1000 sq. ft	1000 sq. ft	1000 sq. ft				400 sq. ft	1000 sq. ft				Available Lens Patterns: 360°, 180°, Aisle, Half Aisle				Available Lens Patterns: 360°, 180°, Aisle, Half Aisle				Available Lens Patterns: 360°, 180°, Aisle, Half Aisle							
Mounting Height	8ft - 12ft		8ft - 12ft		8ft - 12ft	8ft - 12ft	8ft - 12ft	Standard Wallbox	Standard Wallbox	Standard Wallbox				Standard Wallbox	Standard Wallbox				High Mount Lens: 30 ft outdoor / 45 ft indoor, Low Mount Lens: 16 ft				High Mount Lens: 30 ft outdoor / 45 ft indoor, Low Mount Lens: 16 ft				High Mount Lens: 30 ft outdoor / 45 ft indoor, Low Mount Lens: 16 ft							
Voltage	24VDC		24VDC		24VDC	24VDC	24VDC	120/277V or 347V	120/277V or 347V	24V or 120/277V or 347V	120/277V or 347V	24V or 120/277V	24V or 120/277V or 347V	120/277V	24VDC or 120-480VAC				24VDC or 120-480VAC				24VDC or 120/277/347VAC or 208/240VAC or 480VAC											
Dimming	No		No		No	No	No	Yes (0-10V)	Yes (0-10V)	No				No	Yes (0-10V)				No															
Operating Environment	32° to 104°F (0° to 40°C)		32° to 104°F (0° to 40°C)		32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)				32° to 104°F (0° to 40°C)	32° to 104°F (0° to 40°C)				Indoor: 32° to 149°F (0° to 65°C); Outdoor: -40° to 149°F (-40° to 65°C)				Indoor: 32° to 149°F (0° to 65°C); Outdoor: -40° to 149°F (-40° to 65°C)				Indoor: 32° to 149°F (0° to 65°C); Outdoor: -40° to 149°F (-40° to 65°C)							
PowerPack	UVPP or MP series (not included)		UVPP or MP series (not included)		UVPP or MP series (not included)	UVPP or MP series (not included)	UVPP or MP series (not included)	Not required	Not required	24V version requires UVPP or MP series (not included)	Not required	24V version requires UVPP or MP series (not included)	24V version requires UVPP or MP series (not included)	24V version requires UVPP or MP series (not included)				24V version requires UVPP or MP series (not included)				24V version requires UVPP or MP series (not included)												
Photocell	Yes (-RP version)		Yes (-RP version)		Yes (-RP version)	Yes (-RP version)	Yes	Yes	Yes	Yes				Yes	Yes				Yes (Upward/Downward)				Yes (Upward/Downward)				Yes (Upward/Downward)							
Relay	Yes (-RP version)		Yes (-RP version)		Yes (-RP version)	Yes (-RP version)	Yes	No	No	Yes (24V version)	No	Yes (24V version)	Yes (24V version)	No				No				Yes (24V version)												
Colors	Off white		Off white		Off white	Off white	Off white	White, Ivory, Light Almond, Gray, Black	White, Ivory, Light Almond, Gray, Black	White, Ivory, Light Almond, Gray, Black				White, Ivory, Light Almond, Gray, Black	White, Ivory, Light Almond, Gray, Black				White, Black, Gray				White, Black, Gray				White, Black, Gray							
Certifications	UL and cUL, Title 24		UL and cUL, Title 24		UL and cUL, Title 24	UL and cUL, Title 24	UL and cUL, Title 24	UL and cUL, Title 24	UL and cUL, Title 24	UL and cUL, Title 24				UL and cUL, Title 24	UL and cUL, Title 24				UL STD 508, UL STD 244A, Title 24				UL STD 508, UL STD 244A, Title 24				UL STD 508, UL STD 244A, Title 24							
Warranty	5-year		5-year		5-year	5-year	5-year	5-year	5-year	5-year				5-year	5-year				5-year				5-year				5-year							