

# AHG Series

LED Hazardous Location Luminaire



Enclosed and Gasketed for  
Class 1, Division 2 environments

Non-porous gasketing  
ensures a tight seal


Latches, Polyacetal (POM) Standard  
(Stainless Steel, Tamper resistant  
options available)

Durable Fiberglass  
UL 5VA Housing


F1 Weatherability rating, suitable  
for indoor or outdoor use

Lens Options available in  
Clear or Diffuse Acrylic or  
Polycarbonate

Available in 4 or 8 foot lengths



Up to 8,000 nominal lumens



Up to 16,000 nominal  
lumens



Surface  
Mounting  
Brackets  
(Included)

# Safe, Reliable & Improves Operating Costs

The Albeo® AHG LED fixture is an enclosed and gasketed hazardous location LED product. AHG is standard Class 1, Division 2, Groups A, B, C and D. It is offered in 4' and 8' lengths with lumen packages ranging from 5,000-16,000 lumens.

## Applications

- Chemical Processing Facilities
- Power Generation Facilities
- Ethanol Refineries
- Wastewater and Water Treatment Facilities
- Manufacturing Facilities
- Petroleum Refineries

**Size:** 4ft, 8ft

**Lens:** Diffused and Clear Acrylic, and Polycarbonate

**Housing:** Formed UL 5VA Fiberglass

**Finish:** White Painted Parts

**Color Temp:** 3000K, 3500K, 4000K and 5000K

**CRI:** 80

**Lumen Output:** 5,000 to 16,000

**Dimming:** Continuous 0-10V Dimming

**Voltage:** 120-277V; 347V; 480V



## Want to learn more?

For Specific product technical questions, contact: [lightingproinfo@currentlighting.com](mailto:lightingproinfo@currentlighting.com)