

C65 Series -LSCS

Demanding High Bay

Where Industrial Strength Meets Sleek Design.

Tough
never
looked
this good



1 Versatile Performance

- 120-347V with 0-10V dimming to 10%
- Suitable for -40°C up to 65°C ambie
- LPW up to 161
- 10KV standard offering

2 Switchable Lumen & CCT

- 3 Lumen Outputs
 - Size 1: Switchable 16/19/**24K** Lumens
 - Size 2: Switchable 27/30/**33K** Lumens
- Switchable **4000K**/5000K, 80 CRI

Bold indicates default setting

3 Field Installable Sensor

- Easy Installation
- Optional Remote

4 Construction

- Lens options: diffused polycarbonate wide and medium. Glass wide. All lenses are tested for IK07
- Die cast aluminum housing, IK10 rated and Salt Fog tested for +200hr
- Thermally separated electronics and driver for best life rating
- Light weight and compact making it easy to handle and install

5 Design Life

- Driver design life +50,000hr at 65°C
- LED life: L70 of >100,000hr at 25°C

6 Two Sizes

Size	Length Inches (mm)	Width Inches (mm)	Height Inches (mm)	Weight lbs (kg)
1	18.35" (466)	12.32" (313)	2.11" (53.5)	10 lb (4.5)
2	23.31" (592)	13.15" (334)	2.11" (53.5)	15 lb (6.8)



C65 Series -LSCS

Demanding High Bay

C65 offers the right combination of options in each stocked SKU to satisfy your job needs and beyond. With ambient of 65C, IP65, selectable lumens and CCT, field-installable sensors, factory integrated emergency battery and mounting accessories, C65 is the ideal solution for a wide range of industrial and demanding applications. Not to mention a driver life of 50K hrs at 65°C.



Size	Size 1: 18.35" L x 12.32" W x 2.11" H Size 2: 23.31" L x 3.15" W x 2.11" H	CCT Offering	Switchable 4000K/5000K
Lumen Range	Switchable 16,000 - 33,000 lumens	CRI Offering	80
Beam Distributions	Wide and Medium	Certifications	UL/cUL, DLC, (DLC Premium - Medium Distribution)
Housing	Die cast aluminum	Voltage Offering	120-347V
Finish	Powder Coat, White	Dimming	0 - 10V Dimming to 10%
Lens	Diffused Polycarbonate and Glass lens	Options/Accessories	Surface Mount Kit, Pendant Mount Kit, PIR Sensor, Remote, Factory Integrated Emergency Battery, Wire Guards
Wattage Range	100-210W		
Ambient Temp. Range	-40°C up to 65°C		



Want to learn more?

Scan the QR code to learn more about the C65 Series - LSCS