

CLB

LINEAR HIGH BAY



CLB

LINEAR HIGH BAY



Cable Mount



Surface Mount (Optional)



Pendant Mount (Optional)

Features and Benefits

- Lumen packages ranging from 10,000 to 57,000 lumens
- Wide (standard) lens distribution options
- -40°C to 50°C ambient operating temperatures
- 4000/5000K options with 80 CRI
- IP4X Rated
- IK10 Impact Rated
- DLC® (DesignLights Consortium) Qualified. Please refer to the DLC website for specific product qualifications at www.designlights.org



CATALOG NUMBER	NOMINAL LUMENS	COLOR	DELIVERED LUMENS	WATTAGE	LPW	Pallet QTY
CLB2-40LX-W-EDU	2' LX (10,000)	4000K	10,527	75.9	139	78
CLB2-50LX-W-EDU		5000K	10,477	73.7	142	78
CLB2-40MM-W-EDU	2' MM (14,000)	4000K	15,091	100.2	151	78
CLB2-50MM-W-EDU		5000K	13,717	98.9	139	78
CLB2-40MH-W-EDU	2' MH (24,000)	4000K	20,831	153.9	135	78
CLB2-50MH-W-EDU		5000K	22,297	148.7	150	78
CLB2-40MV-W-EDU	2' MV (30,000)	4000K	26,364	191.2	138	52
CLB2-50MV-W-EDU		5000K	29,674	201	148	52
CLB4-40MX-W-EDU	4' MX (36,000)	4000K	35,051	240.9	145	39
CLB4-50MX-W-EDU		5000K	37,145	242	154	39
CLB4-40HM-W-EDU	4' HM (42,000)	4000K	42,810	299	143	39
CLB4-50HM-W-EDU		5000K	44,006	301.6	146	39
CLB4-40HH-W-EDU	4' HH (57,000)	4000K	57,047	388.2	147	52
CLB4-50HH-W-EDU		5000K	55,637	393.7	141	52

Ordering Information

EXAMPLE CLB4-40MH-N-EDU

YOUR ORDER

CLB		-		W		-		ED		-		VOLTAGE		OPTIONS	
MODEL	SIZE	COLOR TEMP		LUMEN OUTPUT		DISTRIBUTION		DRIVER							
CLB Linear High Bay	2 2' 4 4'	40	4000K	LX	2' (10,000)	W	Wide	ED	0-10V Dimming	U	Universal (120-277V)	C6TL20_	6' Cord and Twist-Lock™ Plug 20A (Add Voltage 1=120, 2=277, 4=480)		
		50	5000K	MM	2' (14,000)					HV	High Voltage (347-480V)	C6TL15_	6' Cord and Twist-Lock™ Plug 15A (Add Voltage 1=120, 2=277)		
				MH	2' (24,000)							F3C5	5' Cord, 3-Wire		
				MV	2' (30,000)							F4C5	5' Cord, 4-Wire		
				MX	4' (36,000)							F5C5	5' Cord, 5-Wire		
				HM	4' (42,000)							F6C5	5' Cord, 6-Wire		
				HH	4' (57,000)							C388	3-Wire Flex		
												C488	4-Wire Flex		
												C588	5-Wire Flex		
												C688	6-Wire Flex		

ACCESSORIES (ORDER SEPARATELY)	
LHVQM5	Aircraft Cable, 5' Pair
LHVQM10	Aircraft Cable, 10' Pair
CLB-SMB	Surface Mount Bracket Kit

- 1 WSP360/A sensor option will use HCS WASP End Mount Sensor
- 2 WSPD360/A sensor option will use HCS Dimming WASP End Mount Sensor
- 3 WSPDBT360/A sensor option will use HCS Bluetooth WASP End Mount Sensor
- 4 FSP221B-FSPL7 sensor option will use the Wattstopper FSP-221B end mount sensor
- 5 OSFHU-360/A sensor options will use the Leviton OSFHU-HTW end mount sensor
- 6 HB011-360/A sensor options will use the Leviton HB011-PDX end mount sensor

CONTROL OPTIONS	
<u>Standalone</u>	
WSP360	On/ Off WASP End Mount 360° Lens ¹
WSPA	On/ Off WASP End Mount Aisle Lens ¹
WSPD360	Dimming WASP End Mount 360° Lens ²
WSPDA	Dimming WASP End Mount Aisle Lens ²
WSPDBT360	BT Dimming WASP, Occupancy/Daylight Sensor, 360° Lens ³
WSPDBTA	BT Dimming WASP, Occupancy/Daylight Sensor, Aisle Lens ³
<u>Third-Party Control Options</u>	
FSP221B-FSPL7	Dimming Occupancy/Daylight Sensor, 1-relay, 360 lens, 120-480V ⁴
OSFHU-360	On/ Off Occupancy Sensor, 360 Lens, 120-347V Only ⁵
OSFHU-A	On/ Off Occupancy Sensor, Aisle Lens, 120-347V Only ⁵
HB011-360	Dimming Occupancy Sensor, 360 Lens, 120-277V Only ⁶
HB011-A	Dimming Occupancy Sensor, Aisle Lens, 120-277V Only ⁶