CLH-LSCS

LINEAR HIGH BAY

Versatile Performance

- •120-277V with 0-10V dimming to 10%
- Suitable for -40°C up to 50°C ambient
- LPW up to 159

Field Installable Sensor

- Easy Installation
- Optional Remote

Switchable Lumen & CCT

- 3 Lumen Outputs Size 1: Switchable 15K / 18K / 24K Lumens Size 2: Switchable 24K / 30K/ 36K Lumens
- Switchable 4000K/5000K, 80 CRI Bold indicates default setting

Two Sizes

Size	Length Inches (mm)	Width Inches (mm)	Height Inches (mm)	Weight lbs (kg)
1	23.00" (584.2)	10.25" (260.4)	1.75" (44.5)	4.6 lb (2.1)
2	3100" (7874)	10.25" (260.4)	175" (44.5)	64 lb (29)

Optics

- Diffused Polycarbonate Lens
- Narrow (55°), Medium (90°) and Wide (120°) Ships with medium distribution. Narrow and wide distributions achieved through field installed lens accessory
- IK08

V-Hooks and 3-ft. Chain Included



See Spec sheet for additional mounting options and accessories



Size 2

CLH-LSCS

LINEAR HIGH BAY

The CLH offers the right combination of options in each stocked SKU to satisfy your job needs. With 120–277V, selectable lumens and CCT, field-installable sensors, factory integrated emergency battery and mounting accessories, the CLH is the ideal solution for a wide range of industrial and commercial applications up to 39 ft. mounting height.

Size Size 1: 23" L x 10.25" W x 1.75" H

Size 2: 31" L x 10.25" W x 1.75" H

Lumen Range Switchable 15,000 - 36,000 lumens

Beam Distributions Narrow (55°), Medium (90°) and

Wide (120°)

Housing Steel

Finish Powder Coat, White

Lens Diffused Polycarbonate

Wattage Range 95-242W

Ambient Temp. Range -40°C up to 50°C

CCT Offering Switchable 4000K/5000K

CRI Offering 80

Certifications UL/cUL, DLC, (DLC Premium -

Medium Distribution)

Voltage Offering 120 - 277V

Dimming 0 - 10V Dimming to 10%

Options/Accessories Surface Mount Kit, Pendant Mount

Kit, PIR Sensor, Remote, Factory Integrated Emergency Battery, Wire

Guards

















Surface Mount K

Pendant Mount Kit



