

---

# Current

---

INDUSTRIAL LINE-UP GUIDE

Quickly find the best fit

---

**Columbia**  
LIGHTING

Explore our comprehensive range of lighting solutions designed to meet your unique needs in commercial and industrial spaces.





VALUE

SPECIFICATION

## CLH

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>In stock</li> <li>Field switchable performance</li> <li>Less SKUs cover more needs</li> </ol>	
<b>MARKET</b> Industrial	
<b>FOCUSED APPLICATION</b> Manufacturing, Warehouse, Distribution Center	
<b>Max Lumens</b>	36,000
<b>Max LPW</b>	159
<b>Temp</b>	-40° to 50°C

## PELOTON™ PEL

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>Best glare control, visual comfort</li> <li>Easy replacement for legacy form factors</li> <li>Highest max ambient temperature</li> </ol>	
<b>MARKET</b> Commercial	
<b>FOCUSED APPLICATION</b> Retail, Convention Center, Gym/Arena	
<b>Max Lumens</b>	60,000
<b>Max LPW</b>	182
<b>Temp</b>	-40° to 60°C

## PELA

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>Compact, light weight design</li> <li>Bulk job pack, quick one-installer ease</li> <li>Less jobsite waste, high sustainability</li> </ol>	
<b>MARKET</b> Industrial	
<b>FOCUSED APPLICATION</b> Manufacturing, Warehouse, Distribution Center	
<b>Max Lumens</b>	60,000
<b>Max LPW</b>	190
<b>Temp</b>	-40° to 50°C

## ECHELĂN ECH

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>Highest mounting height</li> <li>Compact design, easy to handle</li> <li>Lowest cost of ownership</li> </ol>	
<b>MARKET</b> Industrial	
<b>FOCUSED APPLICATION</b> Manufacturing, Retail, Large Indoor Space	
<b>Max Lumens</b>	90,000
<b>Max LPW</b>	201
<b>Temp</b>	-40° to 55°C



VALUE

SPECIFICATION

## CRN2

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ul style="list-style-type: none"> <li>1. In stock/built for your convenience</li> <li>2. Field switchable performance (beam, CCT, lumen)</li> <li>3. Less SKUs cover more needs</li> </ul>	
<b>MARKET</b>	
Industrial / Commercial	
<b>FOCUSED APPLICATION</b>	
Warehouse, Manufacturing, Garden Center, Food Prep Areas, Auto Services, Car Wash	
<b>Max Lumens</b>	38,000
<b>Max LPW</b>	178
<b>Temp</b>	-40° to 55°C

## UTILIBAY™ UTB2

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ul style="list-style-type: none"> <li>1. Built to your specifications</li> <li>2. Designed for optimal quality</li> <li>3. Complete control selection</li> </ul>	
<b>MARKET</b>	
Industrial / Commercial	
<b>FOCUSED APPLICATION</b>	
Arena, Gymnasium, Auditorium, Convention Center, Retail, Manufacturing	
<b>Max Lumens</b>	30,000
<b>Max LPW</b>	162
<b>Temp</b>	-40° to 65°C

## SAVVANO™ SAV

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ul style="list-style-type: none"> <li>1. Blending utility with aesthetics</li> <li>2. Architectural styling and decorative finishes</li> <li>3. Stand-alone controls enabled</li> </ul>	
<b>MARKET</b>	
Hospitality / Architectural / Retail	
<b>FOCUSED APPLICATION</b>	
Lobbies, Show Room, Auditorium, Gymnasium, Cafetorium	
<b>Max Lumens</b>	28,000
<b>Max LPW</b>	123
<b>Temp</b>	-40° to 50°C

# VAPORTITE (ENCLOSED & GASKETED)





Click on product images for more complete details including sensor and NX Lighting Controls options.




VALUE

SPECIFICATION

## CVT-LSCS

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>1. Contractor focused</li> <li>2. Field switchable performance</li> <li>3. Less SKUs cover more needs</li> </ol>	
<b>MARKET</b>	
Industrial	
<b>FOCUSED APPLICATION</b>	
Manufacturing, Transit Stations, Cold Storage, Food Processing, Car Washes, Washdown Environments, Prisons	
<b>Max Lumens</b>	12,000
<b>Max LPW</b>	148
<b>Temp</b>	-40° to 45°C
 	

## LXEN

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>1. Slim form factor for confined spaces</li> </ol>	
<b>MARKET</b>	
Industrial	
<b>FOCUSED APPLICATION</b>	
Manufacturing, Transit Stations, Cold Storage, Food Processing, Car Washes, Washdown Environments, Prisons, Under-canopy, Garden Centers	
<b>Max Lumens</b>	4,200
<b>Max LPW</b>	150
<b>Temp</b>	-20° to 50°C
  	

## LXEM/LXEP/HEM

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>1. Widest selection of options</li> <li>2. Parking deck optic (LXEP)</li> <li>3. Hazardous rated versions (HEM)</li> </ol>	
<b>MARKET</b>	
Industrial	
<b>FOCUSED APPLICATION</b>	
Manufacturing, Transit Stations, Tunnels, Cold Storage, Food Processing, Car Washes, Parking Garages, Chemical Facilities, Washdown Environments, Prisons	
<b>Max Lumens</b>	22,400
<b>Max LPW</b>	147
<b>Temp</b>	-20° to 50°C
  	

## LXEW

<b>FEATURES</b> +++	<b>BUDGET</b> \$\$\$
<ol style="list-style-type: none"> <li>1. Wide body for high mounting height applications</li> </ol>	
<b>MARKET</b>	
Industrial	
<b>FOCUSED APPLICATION</b>	
Manufacturing, Transit Stations, Tunnels, Cold Storage, Food Processing, Car Washes, Washdown Environments	
<b>Max Lumens</b>	38,000
<b>Max LPW</b>	136
<b>Temp</b>	-40° to 50°C
  	



VALUE

SPECIFICATION

## CRN2

<b>FEATURES</b>	<b>BUDGET</b>
+++	\$\$\$

---

- 1. IP65; up to 55° ambient
- 2. Field installable sensor
- 3. Field switchable performance (beam, lumen, CCT)

---

**MARKET**

Industrial / Commercial

---

**FOCUSED APPLICATION**

Warehouse, Manufacturing,  
Garden Center, Food Prep Areas,  
Mechanics/Garage, Car Wash,

---

<b>Max Lumens</b>	38,000
<b>Max LPW</b>	178
<b>Temp</b>	-40° to 55°C

tradeSELECT®




## C65

<b>FEATURES</b>	<b>BUDGET</b>
+++	\$\$\$

---

- 1. IP65; up to 65° ambient
- 2. Field installable sensor
- 3. Field switchable performance (lumen, CCT)

---

**MARKET**

Industrial / Commercial

---

**FOCUSED APPLICATION**

Manufacturing, Industrial Heavy Machinery,  
Warehouse / Service Bays, Ice Rinks / Gymnasium,  
Under Canopy / Airport Hangars—  
*Any Space Openly Connected To Outdoor,*  
Cold Storage, Natatoriums, Food Service

---

<b>Max Lumens</b>	33,000
<b>Max LPW</b>	161
<b>Temp</b>	-40° to 65°C



## HEM

<b>FEATURES</b>	<b>BUDGET</b>
+++	\$\$\$

---

- 1. Hazardous Class 1, Div 2 rated
- 2. Impact resistant lenses

---

**MARKET**

Hospitality / Architectural / Retail

---

**FOCUSED APPLICATION**

Manufacturing, Transit Stations, Tunnels,  
Cold Storage, Food Processing, Car Washes,  
Parking Garages, Chemical Facilities,  
Washdown Environments, Prisons

---

<b>Max Lumens</b>	16,300
<b>Max LPW</b>	123
<b>Temp</b>	-40° to 40°C