

# VAPORTITE (ENCLOSED & GASKETED)



Click on product images for more complete details including sensor and NX Lighting Controls options.

VALUE

SPECIFICATION

## CVT-LSCS

|   |                         |
|---|-------------------------|
| <b>FEATURES</b><br>+++  | <b>BUDGET</b><br>\$\$\$ |
| <ol style="list-style-type: none"> <li>1. Contractor focused</li> <li>2. Field switchable performance</li> <li>3. Less SKUs cover more needs</li> </ol> |                         |
| <b>MARKET</b>   |                         |
| Industrial  |                         |
| <b>FOCUSED APPLICATION</b>  |                         |
| Manufacturing, Transit Stations, Cold Storage, Food Processing, Car Washes, Washdown Environments, Prisons  |                         |
| <b>Max Lumens</b>   | 12,000                  |
| <b>Max LPW</b>  | 148                     |
| <b>Temp</b>   | -40° to 45°C            |
|   |                         |

## LXEN

|  |                         |
|--|-------------------------|
| <b>FEATURES</b><br>+++   | <b>BUDGET</b><br>\$\$\$ |
| <ol style="list-style-type: none"> <li>1. Slim form factor for confined spaces</li> </ol>  |                         |
| <b>MARKET</b>  |                         |
| Industrial   |                         |
| <b>FOCUSED APPLICATION</b>   |                         |
| Manufacturing, Transit Stations, Cold Storage, Food Processing, Car Washes, Washdown Environments, Prisons, Under-canopy, Garden Centers |                         |
| <b>Max Lumens</b>  | 4,200                   |
| <b>Max LPW</b>   | 150                     |
| <b>Temp</b>  | -20° to 50°C            |
|  |                         |

## LXEM/LXEP/HEM

|   |                         |
|---|-------------------------|
| <b>FEATURES</b><br>+++  | <b>BUDGET</b><br>\$\$\$ |
| <ol style="list-style-type: none"> <li>1. Widest selection of options</li> <li>2. Parking deck optic (LXEP)</li> <li>3. Hazardous rated versions (HEM)</li> </ol> |                         |
| <b>MARKET</b>   |                         |
| Industrial  |                         |
| <b>FOCUSED APPLICATION</b>  |                         |
| Manufacturing, Transit Stations, Tunnels, Cold Storage, Food Processing, Car Washes, Parking Garages, Chemical Facilities, Washdown Environments, Prisons         |                         |
| <b>Max Lumens</b>   | 22,400                  |
| <b>Max LPW</b>  | 147                     |
| <b>Temp</b>   | -20° to 50°C            |
|   |                         |

## LXEW

|  |                         |
|--|-------------------------|
| <b>FEATURES</b><br>+++   | <b>BUDGET</b><br>\$\$\$ |
| <ol style="list-style-type: none"> <li>1. Wide body for high mounting height applications</li> </ol>       |                         |
| <b>MARKET</b>  |                         |
| Industrial   |                         |
| <b>FOCUSED APPLICATION</b>   |                         |
| Manufacturing, Transit Stations, Tunnels, Cold Storage, Food Processing, Car Washes, Washdown Environments |                         |
| <b>Max Lumens</b>  | 38,000                  |
| <b>Max LPW</b>   | 136                     |
| <b>Temp</b>  | -40° to 50°C            |
|  |                         |