

SLING

Luminaire / Pole Combination



Sling Series Luminaire

- Compact sleek design with multiple configurations and simple installation
- Single & Double 180 deg. Configurations 4000K CCT (70 CRI)
- Type 3 & 4W Distributions
- Dark Bronze Powder Paint (textured)

One of our most popular area lights paired with our most popular poles!

SSS Series Poles

- Square Straight Steel Construction
- 4" Square x 0.125" Wall Thickness
- 20' and 25' Lengths
- Pole Base Accommodates 8"-10" Bolt Circles using Four 3/4" Diameter Anchor Bolts
- Dark Bronze Powder Paint (textured)
- Optional Vibration Damper Available as Accessory



10-Day Quick Shipments

- All Product Manufactured and Ship From Christiansburg, VA Within 10 Days
- Consolidated Shipment – Everything Arrives On One Truck!
- All Configurations Available Less Anchor Bolts
- Stocked Anchor Bolts & Templates Available for Advanced Foundation Construction

COMPLETE FIXTURE, POLE, ANCHOR BOLTS/BASE COVERS, POLE CAPS AND TEMPLATE



ORDERING INFORMATION

Catalog Number	Pole	Single or Double	Fixture	Distribution
ASL1-100-4K7-3-S20	20' Square Straight Steel	Single Head	ASL1-160L-100-4K7	3
ASL1-100-4K7-4W-S20	20' Square Straight Steel	Single Head	ASL1-160L-100-4K7	4W
ASL1-100-4K7-3-S20-2X	20' Square Straight Steel	Double Head (180°)	ASL1-160L-100-4K7	3
ASL1-100-4K7-4W-S20-2X	20' Square Straight Steel	Double Head (180°)	ASL1-160L-100-4K7	4W
ASL1-100-4K7-3-S25	25' Square Straight Steel	Single Head	ASL1-160L-100-4K7	3
ASL1-100-4K7-4W-S25	25' Square Straight Steel	Single Head	ASL1-160L-100-4K7	4W
ASL1-100-4K7-3-S25-2X	25' Square Straight Steel	Double Head (180°)	ASL1-160L-100-4K7	3
ASL1-100-4K7-4W-S25-2X	25' Square Straight Steel	Double Head (180°)	ASL1-160L-100-4K7	4W
ASL1-135-4K7-3-S20	20' Square Straight Steel	Single Head	ASL1-160L-135-4K7	3
ASL1-135-4K7-4W-S20	20' Square Straight Steel	Single Head	ASL1-160L-135-4K7	4W
ASL1-135-4K7-3-S20-2X	20' Square Straight Steel	Double Head (180°)	ASL1-160L-135-4K7	3
ASL1-135-4K7-4W-S20-2X	20' Square Straight Steel	Double Head (180°)	ASL1-160L-135-4K7	4W
ASL1-135-4K7-3-S25	25' Square Straight Steel	Single Head	ASL1-160L-135-4K7	3
ASL1-135-4K7-4W-S25	25' Square Straight Steel	Single Head	ASL1-160L-135-4K7	4W
ASL1-135-4K7-3-S25-2X	25' Square Straight Steel	Double Head (180°)	ASL1-160L-135-4K7	3
ASL1-135-4K7-4W-S25-2X	25' Square Straight Steel	Double Head (180°)	ASL1-160L-135-4K7	4W