

through two different optical technologies, Strike and Micro Strike, which affords the customer the ability to select the ideal distribution for their specific requirements. Now available with a lumen switchable dial option for even more on-site flexibility. Available in round or square form factors.



Consuming only 25 to 50 watts, the Ceileo is designed to replace up to 250 watt HID systems, while reducing maintenance by delivering over 200,000 hours of projected life.

BENEFITS OF THE CEILEO

- Advanced optics for even light distribution and low glare appearance
- Lumen dimmable dial option, allowing for easy, on-site light output adjustments
- Specialty distributions available for unique applications or specific requirements





CEILEO



Advanced Optics

MICROSTRIKE

Micro Strike Optics offer five distinct distribution patterns to illuminate a variety of applications. This optic maximizes target zone illumination with improved uniformity. This, combined with the high lumens per watt, make MicroStrike the perfect choice for most common applications.



Strike Optics allow for maximized spacing and are available in eleven distribution patterns. This makes Strike Optics ideal for unique or specialty applications.



Example: CLO-80L-25-4F-UNV-RD-DBT

Square

ORDERING GUIDE

CATALOG #

MICRO STRIKE

| CLO Ceileo Engine - Watts 80L-25 3200 lumens 80L-39 5000 lumens 80L-50 6000 lumens | LED Color 3K7 3000K, 70CRI 4K7 4000K, 70CRI 5K7 5000K, | - 1 | Optics 2 3 4F 4W | Type 2 Type 3 Type 4 Forward | _ | Voltage UNV 120–277V | | Cold BLT BLS DBT DBS | Black Matte Textured Black Gloss Smooth Dark Bronze Matte Textured Dark Bronze Gloss Smooth | _[| Options LS Lumen Switchable Module |
|--|---|-----|------------------------------|---------------------------------------|---|-------------------------|--|--|---|----|-------------------------------------|
| SUL-50 GOOD lumens | | | 4W | Forward Type 4 Wide | | | | DBS GTT LGS PSS WH' WH: | Dark Bronze Gloss Smooth Graphite Matte Textured Light Grey Gloss Smooth Platinum Silver Smooth White Matte Textured White Gloss Smooth | | |

STRIKE

| Model | _ | Engine | - Watts | _ | LED (| Color | -[| Optics | S |] | Volta | ge | _ | Styl | le Options | -[| Color | |]- | Opti | ons |
|-------|--------|--------|----------------|-----|-------|-----------------|----|--------------------|--------------------------|-------|-------|----------|---|------|------------|----|--------|----------------------------|----|------|---------------------|
| CLO | Ceileo | 18L-25 | | | 3K7 | 3000K, | | 2 | Type 2 | | UNV | 120-277V | | RD | Round | | BLT | Black Matte Textured | | SP | 20KA |
| | | | lumens | | | 70CRI | | 3 | Type 3 | | | | | SQ | Square | | BLS | Black Gloss Smooth | | | Surge |
| | | 18L-39 | | 1 1 | 4K7 | 4000K, | | 4F | Type 4 Forward | | | | | | | | DBT | Dark Bronze Matte Textured | | | Protector |
| | | 401 50 | lumens | | F1/7 | 70CRI | | 4W | Type 4 Wide | | | | | | | | DBS | Dark Bronze Gloss Smooth | | LS | Lumen Switchable |
| | | 18L-50 | 5300 lumens | 1 1 | 5K7 | 5000K, 70CRI | | 5QW | Type V, Square Wide | | | | | | | | GTT | Graphite Matte Textured | | | Module |
| | | | 101110110 | | | , , , , , , , | | 5x5 | Aisle Lighter | | | | | | | | LGS | Light Grey Gloss Smooth | | | |
| | | | | | | | | 5R | Type V, Rectangular | | | | | | | | PSS | Platinum Silver Smooth | | | |
| | | | | | | | | 5QM | Type V, Square | | | | | | | | WHT | White Matte Textured | | | |
| | | | | | | | | | Medium | | | | | | | | WHS | White Gloss Smooth | | | |
| | | | | | | | | 5QN | Type V, Square Narrow | | | | | | | | VGT | Verde Green Textured | | | |
| | | | | | | | 5W | Type V, Round Wide | | | | | | | | | Option | | | | |
| | | | | | | | | FR | Front Row | | | | | | | | CC | Custom Color | | | |



Optional dimmer switch provides customized power output from 100% - 30%

(See installation instructions for more details)





