

EL218 Micro Flood®



# New Wide Flood!




The Micro Flood's compact size, hardy construction, and unique swivel mount ensures superior aiming, quality and uncompromising performance for landscape lighting applications.

And now, due to popular demand, the Micro Flood is available in the new Wide Flood distribution in addition to Spot and Narrow Flood distributions!

## Features and Benefits:

- Unique swivel mount provides superior aiming without loosening over time.
- Die-cast aluminum with powder coat finish for excellent value and rugged service
- 3000K, 4000K and 5000K standard CCT
- Wide Flood has 350mA drive current up to 953 lumens or 550mA to 1,422 lumens
- Wide Flood has main beam candela up to 1066
- IP66 certified to keep dust and moisture out
- High performance PMMA acrylic optic securely attached to internal heat sink for maximum thermal dissipation
- Spot and Narrow Flood distributions are also available



Swivel with locking teeth has 180° range of motion



IP66 silicone gasket between the PMMA acrylic optic and housing keeps moisture out



Large heat sink on the back of the optic keeps the fixture cool

## ORDERING CODE

EL218								
<b>Distribution</b>	<b>Electrical Module</b>			<b>Fixture Options</b>		<b>Control Options</b>		<b>Mounting Options</b>
S Spot	<u>Source</u>	<u>Color Temperature</u>	<u>Voltage</u>	<u>Barn Doors</u>		<b>DIM</b> 0-10V Dimmable driver. Available in 350 or 55mA. IP710 recommended dimmer.		Refer to 120 Volt Mounting Options Spec Sheet <a href="http://cdn.kimlighting.com/content/products/specs/specs_files/kl_120vmounting_spec.pdf">http://cdn.kimlighting.com/content/products/specs/specs_files/kl_120vmounting_spec.pdf</a> for individual mounting options.
F Narrow Flood	8L 8 LEDs	3K 3000K	UV 120 to 277V	BD215BL Black				
W Wide Flood		4K 4200K		BD215DB Dark Bronze				
<b>Fixture</b>	<b>Drive Current</b>			<u>Fixed Hood</u>				
	3 350mA, 10W	5 550mA, 16W		FH215BL Black				
				FH215DB Dark Bronze				
				FH215GR Verde Green				