



# LED Lamps - Directional



## LED GU10 Lamps

The bright white radiance of the Current's LED GU10 lamps isn't just something you see, it's something you feel. For decorative lighting applications, Current's dimmable LED GU10 lamps offer the ideal solution.

### PERFORMANCE HIGHLIGHTS:

GU10 Lamps	
<b>Light Output:</b>	320-500 Lumens
<b>CRI:</b>	80
<b>CCT:</b>	3000K
<b>Efficiency</b>	Up to 90 LPW
<b>Wattage:</b>	4W-5.5W
<b>Life:</b>	25,000 hours L70
<b>Temperature Rating:</b>	-20° to 40° C
<b>Rating:</b>	Damp
<b>Dimming:</b>	Dims from 100% to 10%

### FEATURES:

- Available in 35° beam patterns
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

### BENEFITS:

- Energy + Cost Savings
- For example, using only 4 watts of energy, save over \$85 in energy costs over the rated life of a lamp versus a standard 35-watt halogen lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

### LIMITED WARRANTY

3 Years

### LEARN MORE:

To learn more about saving money and energy, go to [www.LED.com](http://www.LED.com).





# LED Lamps - Directional

## LED GU10 Lamps

CUSTOMER NAME \_\_\_\_\_  
 PROJECT NAME \_\_\_\_\_  
 DATE \_\_\_\_\_ NOTES \_\_\_\_\_

### Directional Lamps (GU10)

Bulb Shape	Base Type	Watts	Order Code	Description	Carton Volts	MOL Qty <sup>2</sup>	Lumens (ln) (Initial)	CBCP	Color Temp (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) <sup>1</sup>	Dim-mable	Location Rating <sup>3</sup>	Beam Angle	Housing Color	Additional Information <sup>4</sup>	
<b>120V GU10</b>																		
MR16	GU10	4	93305604	LED4D/GU10W830/35-6PK	120	24	2.1	320	370	3000K	80	35	25,000	Yes	Damp, Enclosed	35°	White	6 pack
MR16	GU10	5.5	93305605	LED5D/GU10W830/35-6PK	120	24	2.1	500	595	3000K	80	50	25,000	Yes	Damp, Enclosed	35°	White	6 pack

<sup>4</sup> Check dimmer compatibility at [LED.com/dimming](http://LED.com/dimming)

<sup>1</sup> The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

<sup>2</sup> Minimum order quantity = Carton Qty

<sup>3</sup> UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations