Enhance



Application illustation only, subject lamps not used in photo.

LED dimmable candle lamps

For any decorative lighting application, GE's LED dimmable candle lamps are the perfect solution and offer a multitude of wattage options.

LOW-COST OPERATION

- For example, using only 2.2 watts of energy, save over \$21 in energy costs over the rated life of a lamp versus a standard 15-watt incandescent lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80 82
- · Candles have "sparkle" similar to incandescent

COLOR TEMPERATURE

- Halogen-like color
- Available in 2400K, 2700K and 5000K

LONG LIFE

• Up to 15,000 hours rated life (L70)

DIMMABLE

• Dims from 100% to 10%

ENVIRONMENTALLY CONSCIOUS

 These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

(38)

MILL

(38)

GE QUALITY AND RELIABILITY

• 3-year limited warranty

To learn more about saving money and energy, go to **www.gecurrent.com.**

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.



LED dimmable candle lamps



Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty''	MOL (In)	Lumens Initial	СВСР	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status		n Additional Information
Candle	5																
CA11	MED	4	21250	LED4DCAM-C3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	*	Damp	Clear, Bent tip
			23100	LED4DCAM-AGC-2BT	120	6	4.2	300		2700	80	40W	15,000	Yes	*	Damp	All glass, Clear, Bent tip, 2 pack
		4.2	92389	LED4DCAM-W3/827	120	6	4.2	300		2700	80	40W	15,000	Yes	*	Damp	White, Bent tip
		7	21251	LED7DCAM-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	*	Damp	Clear, Bent tip
			23270	LED5DCAM-AGC-2BT	120	6	4.8	500		2700	80	60W	15,000	Yes	*	Damp	All glass, Clear, Bent tip, 2 pack
	CAND	4	21231	LED4DCAC-C3/827	120	6	4.3	300		2700	80	40W	15,000	Yes	*	Damp	Clear, Bent tip
			23090	LED4DCAC-AGC-2BT	120	6	4.3	300		2700	80	40W	15,000	Yes	*	Damp	All glass, Clear, Bent tip, 2 pack
			69109	LED4DCAC-C3/850	120	6	4.3	300		5000	80	40W	15,000	Yes	*	Damp	Clear, Bent tip
		7	21233	LED7DCAC-C3/827	120	6	4.8	500		2700	80	60W	15,000	Yes	*	Damp	Clear, Bent tip
			23265	LED5DCAC-AGC-2BT	120	6	4.8	500		2700	80	60W	15,000	Yes	*	Damp	All glass, Clear, Bent tip, 2 pack
		2.5	22521	LED2DCAC-AGC-2BT	120	6	4.2	200		2700	80	25W	15,000	Yes	*	Damp	Clear, bent tip

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

- * The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 ** Minimum order quantity = 6
 ★ ENERGY STAR* status: ENERGY STAR* certified. Lamps without a "★" are not ENERGY STAR* certified.
 # UL 1993 Environmental Requirements for LED LAMPS
 Location, damp Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
 Location, wet Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.
- Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR[®] is a registered U.S. mark



www.gecurrent.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions. © 2019 GE Current, a Daintree company

65028 (Rev 12/10/2019)