


Suggested Luminaire Applications



EACL



EALS



| SPECIFICATION FEATURES | |
|------------------------|---|
| • | Square Straight Aluminum Shaft |
| • | Dark Bronze finish is Standard |
| • | Shaft Lengths from 10 to 30 feet |
| • | Pole comes drilled as specified for single or multiple Luminaires |
| • | Top Tenon is an available option |
| • | Shipped with Pole: Handhole and Cover, Electrical Grounding Kit and Pole is spirally wrapped with rip cord removal system |
| • | Anchor bolts can be shipped either with pole or separately (if separate, please make the request at time or order) |

Ordering Number Logic (See Pole Selection Table for actual Ordering Numbers)

A S S A

| Product Type | Pole Cross Section | Shaft Shape | Pole Material | Nominal Mounting Height (ft) | Mounting | Shaft Dimensions | | Finish |
|--------------|--------------------|--------------|---------------|------------------------------|--|------------------|---------------------|--|
| | | | | | | Width (in X in) | Wall Thickness (in) | |
| A = Area | S = Square | S = Straight | A = Aluminum | 10 = 10 | DB = Drill holes for mounting two luminaires at 90° | 4 = 4 x 4 | A = 0.125 | DB = Dark Bronze |
| | | | | 12 = 12 | DO = Drill holes for mounting two luminaires at 180° | 5 = 5 x 5 | B = 0.188 | SN = Satin Anodized |
| | | | | 14 = 14 | DQ = Drill holes for four Luminaires | 6 = 6 x 6 | D = 0.250 | |
| | | | | 15 = 15 | SD = Drill Holes for single luminaire | | | |
| | | | | 18 = 18 | TB = Drill holes for three Luminaires at 90° | | | |
| | | | | 20 = 20 | TD = Drill holes for three Luminaires at 120° | | | |
| | | | | 25 = 25 | 2T = 2-3/8 in. OD top tenon | | | |
| | | | | 30 = 30 | 3T = 3 in. OD top tenon | | | |
| | | | | | NOTE: Substitute required mounting designation for ** in ordering number listed in Selection Table. | | | NOTE: If other than a standard finish is required, substitute SN for DB in Ordering Number listed in selection table. |

NOTE: All poles with anchor bolts need to be entered as 2 line items:

1. The line item for the Pole ONLY, will be the corresponding pole SKU + "-LAB" (Less Anchor Bolts). Example: ASSA10XX4ADB-LAB
2. The line item for the Anchor Bolts and Anchor Bolt Template ONLY, will be the corresponding pole SKU + "-BOLT." Example: ASSA10XX4ADB-BOLT

Pole Selection Table

| Ordering Number | Nominal Mounting Height (ft) | Total Luminaire Weight (lbs) | Shaft Width (in x in) | Wall Thickness (in) | Effective Projected Area (sq ft) | | | Bottom OD X Top OD X Length X Thickness (in X in X ft-in x in) |
|-----------------|------------------------------|------------------------------|-----------------------|---------------------|----------------------------------|--------|---------|--|
| | | | | | 80 MPH | 90 MPH | 100 MPH | |
| ASSA10**4ADB | 10 | 100 | 4 x 4 | 0.125 | 10.5 | 8.2 | 6.4 | 36 |
| ASSA12**4ADB | 12 | 100 | 4 x 4 | 0.125 | 8.2 | 6.2 | 4.8 | 41 |
| ASSA14**4ADB | 14 | 85 | 4 x 4 | 0.125 | 6.3 | 4.7 | 3.3 | 46 |
| ASSA15**4BDB | 15 | 100 | 4 x 4 | 0.188 | 9.3 | 7.1 | 6.2 | 67 |
| ASSA18**4BDB | 18 | 80 | 4 x 4 | 0.188 | 5.8 | 4.2 | 2.9 | 78 |
| ASSA18**4DDB | 18 | 100 | 4 x 4 | 0.250 | 8.6 | 5.8 | 4.1 | 96 |
| ASSA20**4BDB | 20 | 50 | 4 x 4 | 0.188 | 4.8 | 3.1 | - | 85 |
| ASSA20**4DDB | 20 | 90 | 4 x 4 | 0.250 | 6.9 | 4.8 | 3.3 | 105 |
| ASSA20**5BDB | 20 | 100 | 5 x 5 | 0.188 | 8.4 | 6 | 4.2 | 105 |
| ASSA20**5DDB | 20 | 100 | 5 x 5 | 0.250 | 12.8 | 9.1 | 6.8 | 132 |
| ASSA25**5BDB | 25 | 60 | 5 x 5 | 0.188 | 4.7 | 2.7 | - | 124 |
| ASSA25**5DDB | 25 | 100 | 5 x 5 | 0.250 | 7.8 | 5.2 | 3.3 | 160 |
| ASSA25**6DDB | 25 | 100 | 6 x 6 | 0.250 | 13.1 | 9.3 | 6.4 | 199 |
| ASSA30**6DDB | 30 | 25 | 6 x 6 | 0.250 | 7.8 | 4.2 | 2.4 | 235 |