

DATE: LOCATION:

TYPE: PROJECT:

CATALOG #:

FLB24 -24" Floodlight Bracket for Pole

MOUNTING ACCESSORY

DESCRIPTION

This is a 24" Floodlight bracket that accommodates a 2 3/8" knuckle mount. The bracket then attaches to the side of a pole using the specified drill pattern

DIMENSIONS & WEIGHT		
Arm Length	24"	
Tenon Height	4.25"	
Tenon Pipe OD	2.38"	
Tenon Piple ID	2.0"	
Weight	16 lbs.	

MOUNTING INSTRUCTIONS

- Position Floodlighting bracket to desired mounting surface with the (2) holes lined up to pre-drilled holes in surface.
- Secure with (2) 1/2-13 screws, (2) 1/2 split washers and (2) 1/2-13 nuts.
- Pull necessary wiring through middle 3/4" hole in bracket and up through tenon.
- · Install end cap.



- Steel
- · Powder Coat Paint Finish

3' SIDE MOUNT BRACKET ASSY 1/2-13 SCREW (2) 7.00 3' SIDE MOUNT BRACKET ASSY SURFACE DRILL PATTERN REFERENCE 2.50 Ø .75 Ø .56 (2) PLCS

ORDERING GUIDE

CATALOG #

ORDERING INFORMATION

Series	
FLB-24	24" Floodlight Bracket for Pole

BLT	Black Matte Textured
BLS	Black Gloss Smooth
DBT	Dark Bronze Matte Textured
DBS	Dark Bronze Gloss Smooth
GTT	Graphite Matte Textured
LGS	Light Grey Gloss Smooth
LGT	Light Grey Matte Textured
PSS	Platinum Silver Smooth
WHT	White Matte Textured
WHS	White Gloss Smooth
VGT	Verde Green Textured
CC	Custom Color

SHIPPING PACKAGE CONTENTS		
Qty	Description	
1	24" FLB Bracket	
1	End Cap	
2	1/2-13 Screw	
2	1/2 Split Washer	
2	1/2-13 Nut	
EPA	.6ft²	
Weight	16 lbs.	

Example: FLB-24-BLT



DATE:	LOCATION:	
TYPE:	PROJECT:	
IIIL.	TROJECT.	

FLB24 -24" Floodlight Bracket for Pole

MOUNTING ACCESSORY

MORE IMAGES



