



LED Lamps - Directional



Selectable PAR Lamps

Current's Selectable PAR lamps allow you to choose the color temperature and beam spread needed for your application using built-in switches, no tools required. PAR38 lamps also have a switch for wattage/lumens, providing ultimate flexibility.



PERFORMANCE HIGHLIGHTS:

Selectable PAR Lamps	
Light Output:	500-1450 Lumens
CRI:	90
Selectable CCT:	2700K/3000K/3500K/4000K/5000K
Efficiency	Up to 100 LPW
Wattage:	PAR20: 5.5W, PAR30: 10W
Selectable Wattage:	PAR38: 9W/12W/15W
Life:	Up to 25,000 hours L70
Temperature Rating:	-20° to 40° C
Location Rating:	PAR20/PAR30: Damp; PAR38: Wet
Dimming:	Dims from 100% to 10%

FEATURES:

Selectable Lamp Options

- SpectraChoice™: Choose between five color temperature levels to achieve the desired tone of white light
- BeamSelect: Choose between Narrow Flood 25° or Wide Flood 40° beam patterns
- LumenChoice®: On PAR38s, choose between three wattage (lumen) levels to optimize light output for each application
- Available in White or Black housing colors
- Halogen-like color with 90 CRI and CEC Title 20 Compliant
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

BENEFITS:

- Selectable lamps provide one lamp for many applications, simplifying project management by streamlining BOMs and greatly reducing inventory
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent or halogen light sources
- Our LED PAR lamps have less heat, UV or infrared in the beam, which reduces the potential for fading of materials and décor, compared to halogen or incandescent lamps

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.

LIMITED WARRANTY

3 Years



Selectable **LED Lamps**

Do more with less.

- *Reduce Inventory*
- *Simplify Projects*
- *Optimize Solutions*





LED Lamps - Directional

LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Selectable PAR20 Lamps



Selectable SpectraChoice™ and BeamSelect Directional Lamps

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	Watts	Lumens (Initial)	Selectable Beam Angle	CBCP	Selectable Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	Location Rating ³	Housing Color	Additional Information	
PAR 20 Selectable																			
PAR20	E26	93322373	LED5DP20W/9SC/BC	120	6	3.4	5.5	500	25° 40°*	1900 800*	2700K 3000K* 3500K 4000K 5000K	90	50	25,000	Yes	Damp	White	CEC Title 20, Enclosed	
PAR20	E26	93322379	LED5DP20B/9SC/BC	120	6	3.4	5.5	500	25° 40°*	1900 800*	2700K 3000K* 3500K 4000K 5000K	90	50	25,000	Yes	Damp	Black	CEC Title 20, Enclosed	

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

* Default settings noted by "*" in tables above



LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Selectable PAR30 Short Neck Lamps



Selectable SpectraChoice™ and BeamSelect Directional Lamps

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	Watts	Lumens (Initial)	Selectable Beam Angle	Selectable CBCP	Selectable Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	Location Rating ³	Housing Color	Additional Information	
PAR 30 Selectable																			
PAR30	E26	93322385	LED10DP30W/9SC/BC	120	6	3.7	10	1000	25° 40°*	3600 1500*	2700K 3000K* 3500K 4000K 5000K	90	75	25,000	Yes	Damp	White	CEC Title 20, Enclosed	
PAR30	E26	93322391	LED10DP30B/9SC/BC	120	6	3.7	10	1000	25° 40°*	3600 1500*	2700K 3000K* 3500K 4000K 5000K	90	75	25,000	Yes	Damp	Black	CEC Title 20, Enclosed	

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

* Default settings noted by "*" in tables above



LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Selectable PAR30 Long Neck Lamps



Selectable SpectraChoice™ and BeamSelect Directional Lamps

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	Watts	Lumens (Initial)	Selectable Beam Angle	Selectable Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	Location Rating ³	Housing Color	Additional Information
PAR 30 Long Neck Selectable																	
PAR30L	E26	93322397	LED10DP30LW/9SC/BC	120	6	4.7	10	1000	25° 40°*	3600 1500*	90	75	25,000	Yes	Damp	White	CEC Title 20, Enclosed
PAR30L	E26	93322403	LED10DP30LB/9SC/BC	120	6	4.7	10	1000	25° 40°*	3600 1500*	90	75	25,000	Yes	Damp	Black	CEC Title 20, Enclosed

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

* Default settings noted by "*" in tables above



LED Lamps - Directional

LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Selectable PAR38 Lamps



Selectable LumenChoice® + SpectraChoice™ and BeamSelect Directional Lamps

Bulb Shape	Base Type	Order Code	Description	Volts	Carton Qty ²	MOL (in)	Selectable Watts	Selectable Lumens (Initial)	Selectable Beam Angle	Selectable CBCP	Selectable Color Temp. (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	Dimmable	Location Rating ³	Housing Color	Additional Information	
PAR 38 Selectable																			
PAR38	E26	93322409	LED/LC/DP38W/9SC/BC	120	6	5.3	9	900	25°	3700	2700K 3000K* 3500K 4000K 5000K	90	75 100 120	25,000	Yes	Wet	White	CEC Title 20, Enclosed	
							12	1200	25°	4700									
							15*	1450*	25°	5400									
PAR38	E26	93322415	LED/LC/DP38B/9SC/BC	120	6	5.3	9	900	25°	3700	2700K 3000K* 3500K 4000K 5000K	90	75 100 120	25,000	Yes	Wet	Black	CEC Title 20, Enclosed	
							12	1200	25°	4700									
							15*	1450*	25°	5400									

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Wet Location - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.

* Default settings noted by "*" in tables above



www.LED.com

© 2025 Current Lighting Solutions, LLC. All rights reserved. GE and the GE monogram are trademarks of the General Electric Company and are used under license. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.