

ORDERING GUIDE

Examples: NOC-1.5RDL-CHNCSCMBL8-930K-MD-DM1NU-WHS-SOL / NOC-1.5RDL-TRM-RBL

CATALOG #

HOUSING

NOC-1.5R				CHN				8			
Series		Function		Housing		Canopy		Mounting		Output	
NOC-1.5R	Noni Cylinder 1.5" Round	DL	Downlight	CHN	Cylinder Housing	CS	Standard	PR	Rigid Stem, Standard ¹	8	8 Watt
		LW	Lensed Wall Wash			CX	Standard with controls	PR_	Rigid Stem, Custom ¹		
						CC	Conduit	P	Swivel Stem, Standard ¹		
						CY	Conduit with Controls	P_	Swivel Stem, Custom ¹		
								CMBL	6ft Black Cord with cable ²		
								CMWH	6ft White Cord with Cable ²		
								CM15BL	15ft Black Cord with cable ²		
								CM15WH	15ft White Cord with Cable ²		
				SU	Surface						
				CRI/CCT							
				927K		90 CRI, 2700K					
				930K		90 CRI, 3000K					
				935K		90 CRI, 3500K					
				940K		90 CRI, 4000K					
				830K		80 CRI, 3000K					
				835K		80 CRI, 3500K					

[illegible]

TRIM

NOC-1.5R		TRM		FRS	
Series	Function	Trim	Reflector Insert Color	Wall Wash Lens 9	
NOC-1.5R	Noni Cylinder 1.5" Round	DL Downlight LW Lensed Wall Wash	TRM Trim	Texture	FRS Frosted
				RWH White	
				RGY Gray	
				RBL Black	
				RGT Graphite	
				RPP Pink Panache	
				RGH Grasshopper	
				Smooth	
				RWHS White	
				RGYS Gray	
				RBLS Black	
				RCOS Copper	
				RAMW Anti-Microbial White	
				Other	
				RX Custom Finish	

Notes:

- 1 Stem length varies by canopy configuration.
See Dimensions section for details
- 2 Cable/Cord can be cut in the field to custom length
- 3 DL Performance based on SOL lens with RWHS
insert finish
- 4 Available only with FRS lens
- 5 Available only when LW functions selected
- 6 DMI required when NX options selected
- 7 Must specify CX or CY canopy.
Not compatible with SU
- 8 For use with DL function. Leave blank for LW function
- 9 For use with LW function. Leave blank for DL function
- 10 See dimensions section for SU
- 11 Not compatible with SU