

# NOC-1.5S

NONI 1.5" SQUARE CYLINDER FAMILY

## ORDERING GUIDE

Examples: NOC-1.5SDL-CHNCSCMBL-SO50930K-DM1NU-GT-FRS/NOC-1.5SDL-TRM-RPP-FRS

CATALOG #

### HOUSING

NOC-1.5S		CHN			Optic Type	
Series/Category/Size/Shape	Function	Housing	Canopy	Mounting		
NOC-1.5S Noni Cylinder Family 1.5" Square	DL Downlight	CHN Cylinder Housing	CS Canopy - Standard CC Canopy - Conduit	CMBL Cable/Cord 6ft Black Cord <sup>2</sup> CMWH Cable/Cord 6ft White Cord <sup>2</sup> CM15BL Cable/Cord 15ft Black Cord CM15WH Cable/Cord 15ft White Cord	PR Stem - Rigid (Standard) Nominal 18" length from cylinder top to ceiling <sup>1</sup> PR_ Stem - Rigid (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" <sup>1</sup> P Stem - Swivel (Standard) Nominal 18" length from cylinder top to ceiling <sup>1</sup> P_ Stem - Swivel (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" <sup>1</sup> SU Surface	Ultra-Smooth Optic SO50 50°
	LW Lensed Wall Wash					Wall Wash Optic LWLW Lensed Wall Wash <sup>3</sup>

CRI/CCT	DM1 Driver Options	Control Options	U Voltage	Cylinder Housing Color	Lens
927K 90 CRI, 2700K 930K 90 CRI, 3000K 935K 90 CRI, 3500K 940K 90 CRI, 4000K 830K 80 CRI, 3000K 835K 80 CRI, 3500K	DM1 0-10V, ELV, TRIAC 1%	N None	U Universal Voltage 120-277V	<b>Texture</b> WH White GY Gray BL Black GT Graphite PP Pink Panache GH Grasshopper <b>Smooth</b> WHS White GYS Gray BLS Black COS Copper AMW Anti-Microbial White <b>Other</b> X Custom Finish	FRS Frosted <sup>4</sup>

### TRIM

NOC-1.5S		TRM	Reflector Insert Color	Reflector Accessory
Series/Category/Size/Shape	Function	Housing		
NOC-1.5S Noni Cylinder Family 1.5" Square	DL Downlight	TRM Trim	<b>Texture</b> RWH White RGY Gray RBL Black RGT Graphite RPP Pink Panache RGH Grasshopper <b>Smooth</b> RWHS White RGYS Gray RBLS Black RCOS Copper RAMW Anti-Microbial White <b>Other</b> RX Custom Finish	FRS Frosted <sup>5</sup>
	LW Lensed Wall Wash			

- Notes:
- 1 Stem length varies by canopy configuration. See Dimensions section for details
  - 2 Cable/Cord can be cut in the field to custom length
  - 3 Available only when "LW" function selected
  - 4 For DL only
  - 5 For LW only