kurt versen
By Prescolite

NOC-1.5S

NONI 1.5" SQUARE CYLINDER FAMILY

DATE: | LOCATION:

TYPE: | PROJECT:

CATALOG #:

ORDERING GUIDE

Examples: NOC-1.5SDL-CHNCSCMBL8-930K-MD-DM1NU-WHS-SOL/NOC-1.5SDL-TRM-RBL

CATALOG #

HOUSING

NOC-1.5S			–	CHN				8	–		–
Series		**Function**		**Housing**	**Canopy**	**Mounting**		**Output**		**CRI/CCT**	
NOC-1.5S	Noni Cylinder 1.5" Square	**DL** Downlight		**CHN** Cylinder Housing	**CS** Standard	**PR**	Rigid Stem, Standard [1]	**8** 8 Watt		**927K**	90 CRI, 2700K
		LW Lensed Wall Wash			**CX** Standard with controls	**PR_**	Rigid Stem, Custom [1]			**930K**	90 CRI, 3000K
					CC Conduit	**P**	Swivel Stem, Standard [1]			**935K**	90 CRI, 3500K
					CY Conduit with Controls	**P_**	Swivel Stem, Custom [1]			**940K**	90 CRI, 4000K
						CMBL	6ft Black Cord with cable [2]			**830K**	80 CRI, 3000K
						CMWH	6ft White Cord with Cable [2]			**835K**	80 CRI, 3500K
						CM15BL	15ft Black Cord with cable [2]				
						CM15WH	15ft White Cord with Cable [2]				
						SU	Surface				

	–			U	–		–
Beam Spread [5]		**Dimming**	**Controls**	**Voltage**		**Cylinder Housing Color**	**Downlight Lens [10]**
VN Very Narrow (.36 SC / 20°)		**DM1** 0–10V 2% [8]	**N** None	**U** Universal Voltage (120–277V)		**Texture**	**SOL** Solite
NR Narrow (.42 SC / 25°)		**PDM** ELV, TRIAC 2%	**NXE** NX Dual RJ45 SmartPORTS, without Sensor [8, 9]			**WH** White	**CLR** Clear
MD Medium (.56 SC / 35°)		**PEQ0E** Lutron Hi-Lume Premier 0.1%	**NXW** NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor [8, 9]			**GY** Gray	**FRS** Frosted
WD Wide (.76 SC / 45°)						**BL** Black	**LIN** Linear Spread (10 x 40°)
SS Square in Square (1.0 SC / 70°)						**GT** Graphite	**HEX** Hexcel Louver
LW Lensed Wall Wash [7]						**PP** Pink Panache	**NON** No Lens
						GH Grasshopper	
						Smooth	
						WHS White	
						GYS Gray	
						BLS Black	
						COS Copper	
						AMW Anti-Microbial White	
						Other	
						X Custom Finish	

TRIM

NOC-1.5S			–	TRM	–		–	FRS
Series		**Function**		**Trim**		**Reflector Insert Color**		**Wall Wash Lens [11]**
NOC-1.5S	Noni Cylinder 1.5" Square	**DL** Downlight		**TRM** Trim		**Texture**		**FRS** Frosted
		LW Lensed Wall Wash				**RWH** White		
						RGY Gray		
						RBL Black		
						RGT Graphite		
						RPP Pink Panache		
						RGH Grasshopper		
						Smooth		
						RWHS White		
						RGYS Gray		
						RBLS Black		
						RCOS Copper		
						RAMW Anti-Microbial White		
						Other		
						RX Custom Finish		

Notes:

1. Stem length varies by canopy configuration. See Dimensions section for details
2. Cable/Cord can be cut in the field to custom length
3. Available with NR or LW optic only
4. DMT driver must be selected for use with 2765T
5. DL Performance based on SOL lens with RWHS insert finish
6. Available only with FRS lens
7. Available only when LW functions selected
8. DM1 required when NX options selected
9. Must specify CX or CY canopy
10. For use with DL function. Leave blank for LW function
11. For use with LW function. Leave blank for DL function

© 2026 HLI Solutions, Inc. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.