

NOC-2.5R

NONI 2.5" ROUND CYLINDER FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOC-2.5RDL-CHNCSP17-930K-MD-DM1NU-BL / NOC-2.5RDL-TRM-RGT-SOL

CATALOG #	
-----------	--

HOUSING

NOC-2.5R		CHN					
Series	Function	Housing	Canopy	Mounting		Output	CRI/CCT
NOC-2.5R Noni Cylinder 2.5" Round	DL Downlight	CHN Cylinder Housing	CS Standard	PR	Rigid Stem, Standard ¹	10 10 Watt	927K 90 CRI, 2700K
	LW Lensed Wall Wash		CX Standard with controls	PR_	Rigid Stem, Custom ¹	17 17 Watt	930K 90 CRI, 3000K
			CC Conduit	P	Swivel Stem, Standard ¹	25 25 Watt	935K 90 CRI, 3500K
			CY Conduit with Controls	P_	Swivel Stem, Custom ¹		940K 90 CRI, 4000K
				CMBL	6ft Black Cord with cable ²		830K 80 CRI, 3000K
				CMWH	6ft White Cord with Cable ²		835K 80 CRI, 3500K
				CM15BL	15ft Black Cord with cable ²		
				CM15W	15ft White Cord with Cable ²		
				SU	Surface		

Beam Spread ³		Dimming	Controls	U Voltage	Cylinder Housing Color
VN Very Narrow (.44 SC / 25°)		DM1 0-10V 1% ^{6,12}	N None	U Universal Voltage (120-277V)	Texture
NR Narrow (.48 SC / 30°)		PDM ELV, TRIAC 1% ¹²	NXE NX Dual RJ45 SmartPORTS, without Sensor ^{6,7}		WH White
MD Medium (.56 SC / 35°)		ERP 0-10V, ELV, TRIAC Dim-to-Dark ⁶	NXW NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ^{6,7,13}		GY Gray
WD Wide (.82 SC / 50°)		PEQOE Lutron Hi-Lume Premier 0.1%			BL Black
XW Extra Wide (1.10 SC / 75°) ⁴					GT Graphite
LW Lensed Wall Wash ⁵					PP Pink Panache
					GH Grasshopper
					Smooth
					WHS White
					GYS Gray
					BLS Black
					COS Copper
					AMW Anti-Microbial White
					Other
					X Custom Finish

TRIM

NOC-2.5R		TRM	Reflector Insert Color	Lens
Series	Function	Trim	Texture	
NOC-2.5R Noni Cylinder 2.5" Round	DL Downlight	TRM Trim	RWH White	SOL Solite ¹⁰
	LW Lensed Wall Wash		RGY Gray	CLR Clear ¹⁰
			RBL Black	FRS Frosted ¹¹
			RGT Graphite	LIN Linear Spread (10 x 40°) ¹⁰
			RPP Pink Panache	HEX Hexcel Louver ¹⁰
			RGH Grasshopper	NON No Lens ¹⁰
			Smooth	
			RWHS White	
			RGYS Gray	
			RBLS Black	
			RCOS Copper	
			RAMW Anti-Microbial White	
			Other	
			RX Custom Finish	

Notes:

- Stem length varies by canopy configuration. See Dimensions section for details
- Cable/Cord can be cut in the field to custom length
- DL Performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW functions selected
- DM1 or ERP required with NX options
- Must specify CX or CY canopy
- Available only with DL function
- Available with all functions. Must be selected with LW
- Available with 25 or 17 watt only
- Not compatible with SU mounting