

NOC-2.5S

NONI 2.5" SQUARE CYLINDER FAMILY

ORDERING GUIDE

Examples: NOC-2.5SDL-CHNCSCMBL-SO60930K-DMINU-GT / NOC-2.5SDL-TRM-RPP-FRS

CATALOG #

HOUSING

NOC-2.5S		CHN					Optic Type	
Series/Category/Size/Shape	Function	Housing	Canopy	Mounting				
NOC-2.5S Noni Cylinder Family 2.5" Square	DL Downlight	CHN Cylinder Housing	CS Canopy - Standard CC Canopy - Conduit	CMBL Cable/Cord 6ft Black Cord ²	CMWH Cable/Cord 6ft White Cord ²	CM15BL Cable/Cord 15ft Black Cord	CM15WH Cable/Cord 15ft White Cord	Ultra-Smooth Optic
	LW Lensed Wall Wash							SO60 60°
				PR Stem - Rigid (Standard) Nominal 18" length from cylinder top to ceiling ¹				Wall Wash Optic
				PR_ Stem - Rigid (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" ¹				LWLV Lensed Wall Wash ³
				P Stem - Swivel (Standard) Nominal 18" length from cylinder top to ceiling ¹				
				P_ Stem - Swivel (Custom) Specify length from cylinder top to ceiling in 1 inch increments from 15" to 60" ¹				
				SU Surface				

CRI/CCT	Driver Options	Control Options	U Voltage	Cylinder Housing Color
927K 90 CRI, 2700K	DM1 0-10V, ELV, TRIAC 1%	N None	U Universal Voltage 120-277V	Texture
930K 90 CRI, 3000K	ERP 0-10V, ELV, TRIAC Dim-to-Dark			WH White
935K 90 CRI, 3500K	PEQOE Lutron Hi-Lume Premier 0.1%			GY Gray
940K 90 CRI, 4000K				BL Black
830K 80 CRI, 3000K				GT Graphite
835K 80 CRI, 3500K				PP Pink Panache
				GH Grasshopper
				Smooth
				WHS White
				GYS Gray
				BLS Black
				COS Copper
				AMW Anti-Microbial White
				Other
				X Custom Finish

TRIM

NOC-2.5S		TRM	Reflector Insert Color	Lens
Series/Category/Size/Shape	Function	Housing		
NOC-2.5S Noni Cylinder Family 2.5" Square	DL Downlight	TRM Trim	Texture	FRS Frosted
	LW Lensed Wall Wash		RWH White	
			RGY Gray	
			RBL Black	
			RGT Graphite	
			RPP Pink Panache	
			RGH Grasshopper	
			Smooth	
			RWHS White	
			RGYS Gray	
			RBLS Black	
			RCOS Copper	
			RAMW Anti-Microbial White	
			Other	
			RX Custom Finish	

- Notes:
- 1 Stem length varies by canopy configuration. See Dimensions section for details
 - 2 Cable/Cord can be cut in the field to custom length
 - 3 Available only when "LW" function selected