

NOC-2.5S

NONI 2.5" SQUARE CYLINDER FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOC-2.5SDL-CHNCSP17-930K-MD-DM1NU-BL / NOC-2.5SDL-TRM-RGT-SOL

CATALOG #	
-----------	--

HOUSING

NOC-2.5S		CHN					
Series	Function	Housing	Canopy	Mounting		Output	CRI/CCT
NOC-2.5S Noni Cylinder 2.5" Square	DL Downlight	CHN Cylinder Housing	CS Standard	PR	Rigid Stem, Standard ¹	10 10 Watt	927K 90 CRI, 2700K
	LW Lensed Wall Wash		CX Standard with controls	PR_	Rigid Stem, Custom ¹	17 17 Watt	930K 90 CRI, 3000K
			CC Conduit	P	Swivel Stem, Standard ¹	25 25 Watt	935K 90 CRI, 3500K
			CY Conduit with Controls	P_	Swivel Stem, Custom ¹		940K 90 CRI, 4000K
				CMBL	6ft Black Cord with cable ²		830K 80 CRI, 3000K
				CMWH	6ft White Cord with Cable ²		835K 80 CRI, 3500K
				CM15BL	15ft Black Cord with cable ²		
				CM15W	15ft White Cord with Cable ²		
				SU	Surface		

Beam Spread		Dimming		Controls		U	Cylinder Housing Color	
						U Universal Voltage (120-277V)	Texture	
VN	Very Narrow (.46 SC / 25°)	DM1	0-10V 1% ^{6,9,10}	N	None		WH	White
NR	Narrow (.50 SC / 30°)	PDM	ELV, TRIAC 1% ¹⁰	NXE	NX Dual RJ45 SmartPORTS, without Sensor ^{6,7}		GY	Gray
MD	Medium (.60 SC / 35°)	ERP	0-10V, ELV, TRIAC Dim-to-Dark ⁶	NXW	NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ^{6,7,11}		BL	Black
WD	Wide (.84 SC / 55°)	PEQ0E	Lutron Hi-Lume Premier 0.1%				GT	Graphite
SS	Square in Square (1.22 SC / 75°)						PP	Pink Panache
LW	Lensed Wall Wash ⁴						GH	Grasshopper
							Smooth	
							WHS	White
							GYS	Gray
							BLS	Black
							COS	Copper
							AMW	Anti-Microbial White
							Other	
							X	Custom Finish

TRIM

NOC-2.5S		TRM	Reflector Insert Color		Lens	
Series	Function	Trim	Texture			
NOC-2.5S Noni Cylinder 2.5" Square	DL Downlight	TRM Trim	RWH	White	SOL	Solite ⁸
	LW Lensed Wall Wash		RGY	Gray	CLR	Clear ⁸
			RBL	Black	FRS	Frosted ⁹
			RGT	Graphite	LIN	Linear Spread (10 x 40°) ⁸
			RPP	Pink Panache	HEX	Hexcel Louver ⁸
			RGH	Grasshopper	NON	No Lens ⁸
			Smooth			
			RWHS	White		
			RGYS	Gray		
			RBLs	Black		
			RCOS	Copper		
			RAMW	Anti-Microbial White		
			Other			
			RX	Custom Finish		

Notes:

- 1 Stem length varies by canopy configuration. See Dimensions section for details
- 2 Cable/Cord can be cut in the field to custom length
- 3 DL Performance based on SOL lens with RWHS insert finish
- 4 Available only with FRS lens
- 5 Available only when LW functions selected
- 6 DM1 or ERP required with NX options
- 7 Must specify CX or CY canopy
- 8 Available only with DL function
- 9 Available with all functions. Must be selected with LW
- 10 Available with 25 or 17 watt only
- 11 Not compatible with SU mounting