

NOC-3.5R

NONI 3.5" ROUND CYLINDER FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOC-3.5RDL-CHNCSP17-930K-MD-DM1NU-BL / NOC-3.5RDL-TRM-RGT-SOL

CATALOG #	
-----------	--

HOUSING

NOC-3.5R		CHN					
Series	Function	Housing	Canopy	Mounting		Output	CRI/CCT
NOC-3.5R Noni Cylinder 3.5" Round	DL Downlight	CHN Cylinder Housing	CS Standard	PR	Rigid Stem, Standard ¹	10 10 Watt	Static 927K 90 CRI, 2700K 930K 90 CRI, 3000K 935K 90 CRI, 3500K 940K 90 CRI, 4000K 830K 80 CRI, 3000K 835K 80 CRI, 3500K Dynamic 1830DT 90 1800K–3000K Dim-to-Warm ^{3,4} 2765T 90 CRI, 2700K–6500K SpectraSync™ Tunable White ^{3,4,5}
	LW Lensed Wall Wash		CX Standard with controls	PR_	Rigid Stem, Custom ¹	17 17 Watt	
			CC Conduit	P	Swivel Stem, Standard ¹	25 25 Watt	
			CY Conduit with Controls	P_	Swivel Stem, Custom ¹		
				CMBL	6ft Black Cord with cable ²		
				CMWH	6ft White Cord with Cable ²		
				CM15BL	15ft Black Cord with cable ²		
				CM15W	15ft White Cord with Cable ²		
				SU	Surface		

Beam Spread ⁶		Dimming		Controls		U	Cylinder Housing Color	
VN	Very Narrow (42 SC / 25°)	DM1	0–10V 1% ^{9,13}	N	None	U	Texture WH White GY Gray BL Black GT Graphite PP Pink Panache GH Grasshopper Smooth WHS White GYS Gray BLS Black COS Copper AMW Anti-Microbial White Other X Custom Finish	
NR	Narrow (50 SC / 30°)	PDM	ELV, TRIAC 1% ¹³	NXE	NX Dual RJ45 SmartPORTS, without Sensor ^{9,10}			
MD	Medium (58 SC / 35°)	ERP	0–10V, ELV, TRIAC Dim-to-Dark	NXW	NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ^{9,10,14}	U Universal Voltage (120–277V)		
WD	Wide (80 SC / 50°)	PEQOE	Lutron Hi-Lume Premier 0.1% ⁹					
XW	Extra Wide (106 SC / 75°) ⁷	SpectraSync						
LW	Lensed Wall Wash ⁸	DMT	0–10V 5% ³					

TRIM

NOC-3.5R		TRM	Reflector Insert Color		Lens	
Series	Function	Trim				
NOC-3.5R Noni Cylinder 3.5" Round	DL Downlight	TRM Trim	Texture		SOL	Solite ¹¹
	LW Lensed Wall Wash		RWH	White	CLR	Clear ¹¹
			RGY	Gray	FRS	Frosted ¹²
			RBL	Black	LIN	Linear Spread (10 x 40°) ¹¹
			RGT	Graphite	HEX	Hexcel Louver ¹¹
			RPP	Pink Panache	NON	No Lens ¹¹
			RGH	Grasshopper		
			Smooth			
			RWHS	White		
			RGYS	Gray		
			RBLs	Black		
			RCOS	Copper		
			RAMW	Anti-Microbial White		
			Other			
			RX	Custom Finish		

Notes:

- Stem length varies by canopy configuration. See Dimensions section for details
- Cable/Cord can be cut in the field to custom length
- 17W max
- Available with NR or LW beam spread only
- DMT driver must be selected for use with 2765T
- DL Performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW function selected
- DM1 or ERP required with NX options
- Must specify CX or CY canopy
- Available only with DL function
- Available with all functions. Must be selected with LW
- Available with 25 or 17 watt only
- Not compatible with SU mounting