

NOC-3.5S

NONI 3.5" SQUARE CYLINDER FAMILY

DATE: LOCATION:

TYPE: PROJECT:

CATALOG #:

ORDERING GUIDE

Examples: NOC-3.5SDL-CHNCSP17-930K-MD-DM1NU-BL / NOC-3.5SDL-TRM-RGT-SOL

CATALOG #

HOUSING

NOC-3.5S		CHN					
Series	Function	Housing	Canopy	Mounting		Output	CRI/CCT
NOC-3.5S	Noni Cylinder 3.5" Square	DL Downlight LW Lensed Wall Wash	CHN Cylinder Housing	CS Standard	PR Rigid Stem, Standard ¹	10 10 Watt	927K 90 CRI, 2700K
	CX Standard Controls			PR_ Rigid Stem, Custom ¹	17 17 Watt	930K 90 CRI, 3000K	
	CC Conduit			P Swivel Stem, Standard ¹	25 25 Watt	935K 90 CRI, 3500K	
	CY Conduit with Controls			P_ Swivel Stem, Custom ¹		940K 90 CRI, 4000K	
				CMBL 6ft Black Cord with cable ²		830K 80 CRI, 3000K	
				CMWH 6ft White Cord with Cable ²		835K 80 CRI, 3500K	
	CM15BL 15ft Black Cord with cable ²						
	CM15W 15ft White Cord with Cable ²						
	SU Surface						
							Dynamic
							1830DT 90 1800K–300K Dim-to-Warm ^{3, 4}
							2765T 90 CRI, 2700K–6500K SpectraSync™ Tunable White ^{3, 4, 5}

Beam Spread ⁶		Dimming		Controls		Voltage		Cylinder Housing Color	
VN	Very Narrow (.38 SC / 25°)	DM1	0–10V 1% ^{9, 13}	N	None	U	Universal Voltage (120–277V)	Texture	
NR	Narrow (.48 SC / 30°)	PDM	ELV, TRIAC 1% ¹³	NXE	NX Dual RJ45 SmartPORTS, without Sensor ^{9, 10}			WH	White
MD	Medium (.58 SC / 35°)	ERP	0–10V, ELV, TRIAC Dim-to-Dark ⁹	NXW	NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ^{9, 10, 14}			GY	Gray
WD	Wide (.84 SC / 50°)	PEQOE	Lutron Hi-Lume Premier 0.1%					BL	Black
SS	Square in Square (.90 SC / 60°)	SpectraSync						GT	Graphite
LW	Lensed Wall Wash ⁷	DMT	0–10V 5% ³				PP	Pink Panache	
							GH	Grasshopper	
							Smooth		
							WHS	White	
							GYS	Gray	
							BLS	Black	
							COS	Copper	
							AMW	Anti-Microbial White	
							Other		
							X	Custom Finish	

TRIM

NOC-3.5S		TRM	Reflector Insert Color		Lens
Series	Function	Trim	Texture		SOL Solite ¹¹ CLR Clear ¹¹ FRS Frosted ¹² LIN Linear Spread (10 x 40°) ¹¹ HEX Hexcel Louver ¹¹ NON No Lens ¹¹
NOC-3.5S	Noni Cylinder 3.5" Square	TRM Trim	RWH	White	
			RGY	Gray	
			RBL	Black	
			RGT	Graphite	
			RPP	Pink Panache	
			RGH	Grasshopper	
			Smooth		
			RWHS	White	
			RGYS	Gray	
			RBLs	Black	
			RCOS	Copper	
			RAMW	Anti-Microbial White	
			Other		
			RX	Custom Finish	

Notes:

- 1 Stem length varies by canopy configuration. See Dimensions section for details
- 2 Cable/Cord can be cut in the field to custom length
- 3 17W max
- 4 Available with NR or LW beam spread only
- 5 DMT driver must be selected for use with 2765T
- 6 DL Performance based on SOL lens with RWHS insert finish
- 7 Available only with FRS lens
- 8 Available only when LW functions selected
- 9 DM1 or ERP required with NX options
- 10 Must specify CX or CY canopy
- 11 Available only with DL function
- 12 Available with all functions. Must be selected with LW
- 13 Available with 25 or 17 watt only
- 14 Not compatible with SU mounting