

NOR-1.5R

NONI 1.5" ROUND RECESSED FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOR-1.5RDL-RHI8-930K-MD-DM1NU-FWHS-SOL / NOR-1.5RDS-TRM-RBL

CATALOG #	
-----------	--

HOUSING

NOR-1.5R			RHI										
Series		Function		Housing		Output		CRI/CCT		Beam Spread ¹			
NOR-1.5R	Noni Recessed 1.5" Round	DL	Downlight	RHI	Remodeler Housing, IC	8	8 Watt	927K	90 CRI, 2700K	VN	Very Narrow (.36 SC / 20°)		
		LW	Lensed Wall Wash					930K	90 CRI, 3000K				
								935K	90 CRI, 3500K				
								940K	90 CRI, 4000K				
								830K	80 CRI, 3000K				
								835K	80 CRI, 3500K				

		N		U									
Dimming		Controls		Voltage		Reflector Flange Color		Downlight Lens ⁴		Accessories			
DM1	0–10V 2%	N	None	U	Universal Voltage (120–277V)	Flanged		SOL	Solite	MP1.5	Mounting Pan		
PDM	ELV, TRIAC 2%					WHS	White	CLR	Clear	RMB	Residential Mounting Bars		
						GYS	Gray	FRS	Frosted				
						BLS	Black	LIN	Linear Spread (10 x 40°)				
						COS	Copper	HEX	Hexcel Louver				
						AMW	Anti-Microbial White	NON	No Lens				
						Flush Mount							
						FT	Flush Mount						

TRIM

NOR-1.5R				TRM					
Series		Function		Trim		Reflector Insert Color		Wall Wash Lens ⁵	
NOR-1.5R	Noni Recessed 1.5" Round	DL	Downlight	TRM	Trim	Texture		FRS	Frosted
		LW	Lensed Wall Wash			RWH	White		
						RGY	Gray		
						RBL	Black		
						RGT	Graphite		
						RPP	Pink Panache		
						RGH	Grasshopper		
						Smooth			
						RWHS	White		
						RGYS	Gray		
						RBLS	Black		
						RCOS	Copper		
						RAMW	Anti-Microbial White		
						Other			
						PX	Custom Finish		

Notes:

- 1 DL performance based on SOL lens with RWHS insert finish
- 2 Available only with FRS lens
- 3 Available only when LW function is selected
- 4 For use with DL function. Leave blank for LW function
- 5 For use with LW function. Leave blank for DL function