

NOR-1.5S

NONI 1.5" SQUARE RECESSED FAMILY

DATE: _____ LOCATION: _____

TYPE: _____ PROJECT: _____

CATALOG #: _____

ORDERING GUIDE

Examples: NOR-1.5SDL-RHI8-930K-MD-DM1NU-FWHS-SOL / NOR-1.5SDS-TRM-RBL

CATALOG #

HOUSING

NOR-1.5S		RHI		CRI/CCT		Beam Spread ¹	
Series	Function	Housing	Output				
NOR-1.5S Noni Recessed 1.5" Square	DL Downlight	RHI Remodeler Housing, IC	8 8 Watt	927K	90 CRI, 2700K	VN	Very Narrow (.36 SC / 20°)
	LW Lensed Wall Wash			930K	90 CRI, 3000K	NR	Narrow (.42 SC / 25°)
				935K	90 CRI, 3500K	MD	Medium (.56 SC / 35°)
				940K	90 CRI, 4000K	WD	Wide (.76 SC / 45°)
				830K	80 CRI, 3000K	SS	Square in Square (1.0 SC / 70°)
				835K	80 CRI, 3500K	LW	Lensed Wall Wash ³

Dimming		Controls		Voltage		Reflector Flange Color		Downlight Lens ⁴		Accessories	
DM1	PDM	N	U								
0–10V 2%	ELV, TRIAC 2%	N None	U Universal Voltage (120–277V)			Flanged		SOL	Solite	MP1.5	Mounting Pan
						WHS White		CLR	Clear	RMB	Residential Mounting Bars
						GYS Gray		FRS	Frosted		
						BLS Black		LIN	Linear Spread (10 x 40°)		
						COS Copper		HEX	Hexcel Louver		
						AMW Anti-Microbial White		NON	No Lens		
						FX Custom Finish					
						Flush Mount					
						FT Flush Mount					

TRIM

NOR-1.5S		TRM		Reflector Insert Color		Wall Wash Lens ⁵	
Series	Function	Trim	Texture				
NOR-1.5S Noni Recessed 1.5" Square	DL Downlight	TRM Trim	RWH White			FRS Frosted	
	LW Lensed Wall Wash		RGY Gray				
			RBL Black				
			RGT Graphite				
			RPP Pink Panache				
			RGH Grasshopper				
			Smooth				
			RWHS White				
			RGYS Gray				
			RBLS Black				
			RCOS Copper				
			RAMW Anti-Microbial White				
			Other				
			RX Custom Finish				

Notes:

- DL performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW function is selected
- For use with DL function. Leave blank for LW function
- For use with LW function. Leave blank for DL function