

NOR-1.5S

NONI 1.5" SQUARE RECESSED FAMILY

DATE: LOCATION:

TYPE: PROJECT:

CATALOG #:

ORDERING GUIDE

Examples: NOR-1.5SDL-RHI8-930K-MD-DM1NU-FWHS-SOL / NOR-1.5SDS-TRM-RBL

CATALOG #

HOUSING

NOR-1.5S		RHI		8		CRI/CCT		Beam Spread ¹	
Series	Function	Housing	Output						
NOR-1.5S	Noni Recessed 1.5" Square	RHI Remodeler Housing, IC	8 8 Watt			927K	90 CRI, 2700K	VN	Very Narrow (.36 SC / 20°)
						930K	90 CRI, 3000K	NR	Narrow (.42 SC / 25°)
						935K	90 CRI, 3500K	MD	Medium (.56 SC / 35°)
						940K	90 CRI, 4000K	WD	Wide (.76 SC / 45°)
						830K	80 CRI, 3000K	SS	Square in Square (1.0 SC / 70°)
						835K	80 CRI, 3500K	LW	Lensed Wall Wash ³

N		U		Reflector Flange Color		Downlight Lens ⁴		Accessories	
Dimming	Controls	Voltage							
DM1	0–10V 2%	N None	U Universal Voltage (120–277V)	Flanged		SOL	Solite	MP1.5	Mounting Pan
PDM	ELV, TRIAC 2%			WHS White		CLR	Clear		
				GYS Gray		FRS	Frosted		
				BLS Black		LIN	Linear Spread (10 x 40°)		
				COS Copper		HEX	Hexcel Louver		
				AMW Anti-Microbial White		NON	No Lens		
				FX Custom Finish					
				Flush Mount					
				FT Flush Mount					

TRIM

NOR-1.5S		TRM		FRS	
Series	Function	Trim	Reflector Insert Color	Wall Wash Lens ⁵	
NOR-1.5S	Noni Recessed 1.5" Square	TRM Trim	Texture	FRS Frosted	
			RWH White		
			RGY Gray		
			RBL Black		
			RGT Graphite		
			RPP Pink Panache		
			RGH Grasshopper		
			Smooth		
			RWHS White		
			RGYS Gray		
			RBLs Black		
			RCOS Copper		
			RAMW Anti-Microbial White		
			Other		
			RX Custom Finish		

Notes:

- DL performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW function is selected
- For use with DL function. Leave blank for LW function
- For use with LW function. Leave blank for DL function