

NOR-2.5R

NONI 2.5" ROUND RECESSED FAMILY

DATE: LOCATION:

TYPE: PROJECT:

CATALOG #:

ORDERING GUIDE

Examples: NOR-2.5RDL-NHN17-930K-MD-DM1NU / NOR-2.5RDS-TRM-FWHS-RBL-SOL

CATALOG #

HOUSING

NOR-2.5R						
Series	Function	Housing	Output	CRI/CCT	Beam Spread ²	
NOR-2.5R Noni Recessed 2.5" Round	Shallow Housing (2" Depth)	NHN New Construction, Non-IC	10 10 Watt	927K 90 CRI, 2700K	VN Very Narrow (.44 SC / 25°)	
	DL Downlight		17 17 Watt	930K 90 CRI, 3000K	NR Narrow (.48 SC / 30°)	
	LWS Lensed Wall Wash, Shallow	NHI New Construction, IC ¹	25 25 Watt	935K 90 CRI, 3500K	MD Medium (.56 SC / 35°)	
	Shallow Housing (3" Depth)	CP Chicago Plenum ¹		940K 90 CRI, 4000K	WD Wide (.82 SC / 55°)	
	LWD Lensed Wall Wash, Deep			830K 80 CRI, 3000K	XW Extra Wide (1.10 SC / 75°) ³	
	AA Adjustable Accent			835K 80 CRI, 3500K	LW Lensed Wall Wash ⁴	

		U	RMB
Dimming	Controls ¹³	Voltage	Accessories
DM1 0–10V 1% ^{5, 14, 15}	N None	U Universal Voltage (120–277V)	RMB Residential Mounting Bars
PDM ELV, TRIAC 1% ^{5, 15}	LV Lutron Vive 0–10V (120–277V)		
ERP 0–10V, ELV, TRIAC Dim-to-Dark ^{5, 15}	NXE NX Dual RJ45 SmartPORTS, without Sensor ¹⁵		
	NXW NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ¹⁵		

TRIM

NOR-2.5R		TRM			
Series	Function	Trim	Reflector Flange Color	Reflector Insert Color	Lens
NOR-2.5R Noni Recessed 2.5" Round	Shallow Housing Compatible	TRM Trim	Flanged	Texture	SOL Solite ⁵
	DS Downlight, Shallow (%–1 1/8" ceiling)		FWHS White	RWH White	CLR Clear ⁵
	DD Downlight, Deep (1 1/4" ceiling only)		FGYS Gray	RGY Gray	FRS Frosted ⁶
	LWS Lensed Wall Wash, Shallow		FBLS Black	RBL Black	LIN Linear Spread (10 x 40°) ^{5, 7}
	Deep Housing Compatible		FCOS Copper	RGT Graphite	HEX Hexcel Louver ^{5, 8}
	LWD Lensed Wall Wash, Deep		FAMW Anti-Microbial White	RPP Pink Panache	NON No Lens ^{5, 7}
	AA Adjustable Accent		FX Custom Finish	RGH Grasshopper	
			Flush Mount	Smooth	
			FT Flush Mount	RWHS White	
				RGYS Gray	
				RBL Black	
				RCOS Copper	
				RAMW Anti-Microbial White	
				Other	
				RX Custom Finish	

Notes:

- Available in 10 or 17 watt outputs
- DL performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW function is selected
- Available only with DL and AA functions
- Available with all functions. Must be selected with LWS and LWD
- Available with DS only
- HEX and NON suitable for damp location only
- Above ceiling access required
- Only available in 17 or 25 watt outputs
- DM1 or ERP required with NX options