

# NOR-2.5S

NONI 2.5" SQUARE RECESSED FAMILY

## ORDERING GUIDE

Examples: NOR-2.5SDL-NHN17-930K-MD-DM1NU / NOR-2.5SDS-TRM-FWHS-RBL-SOL

CATALOG #

### HOUSING

| NOR-2.5S                                 |                                   | Housing  |  | Output     |  | CRI/CCT |  | Beam Spread <sup>5</sup>         |                             |                           |  |                                     |
|--|-----------------------------------|--|--|------------|--|---------|--|----------------------------------|-----------------------------|---------------------------|--|-------------------------------------|
| Series                                   | Function                          |  |  |            |  |         |  |                                  |                             |                           |  |                                     |
| NOR-2.5S<br>Noni Recessed<br>2.5" Square | <b>Shallow Housing (2" Depth)</b> | NHN New Construction,<br>Non-IC<br>NHI New Construction, IC <sup>1</sup><br>CP Chicago Plenum <sup>1</sup> |  | 10 10 Watt | 927K 90 CRI, 2700K<br>930K 90 CRI, 3000K<br>935K 90 CRI, 3500K<br>940K 90 CRI, 4000K<br>830K 80 CRI, 3000K<br>835K 80 CRI, 3500K |         |  | VN Very Narrow<br>(.46 SC / 25°) |                             |                           |  |                                     |
|  | DL Downlight                      |  |  | 17 17 Watt |  |         |  |                                  |                             |                           |  |                                     |
|  | LWS Lensed Wall Wash,<br>Shallow  |  |  | 25 25 Watt |  |         |  |                                  |                             |                           |  |                                     |
|  | <b>Shallow Housing (3" Depth)</b> |  |  |            |  |         |  |                                  |                             |                           |  |                                     |
|  | LWD Lensed Wall Wash,<br>Deep     |  |  |            |  |         |  |                                  |                             |                           |  |                                     |
|  | AA Adjustable Accent              |  |  |            |  |         |  |                                  |                             |                           |  |                                     |
|  |                                   |  |  |            |  |         |  | NR Narrow<br>(.50 SC / 30°)      | MD Medium<br>(.60 SC / 35°) | WD Wide<br>(.84 SC / 55°) | SS Square in Square<br>(1.22 SC / 75°) | LW Lensed<br>Wall Wash <sup>7</sup> |

| Dimming   |  | Controls <sup>13</sup>   |  | U Voltage                         | Accessories                      |
|---|--|--|--|-----------------------------------|----------------------------------|
| DM1 0–10V 1% <sup>8, 14, 15</sup>                     |  | N None   |  | U Universal Voltage<br>(120–277V) | RMB Residential<br>Mounting Bars |
| PDM ELV, TRIAC 1% <sup>8, 14</sup>                    |  | LV Lutron Vive 0–10V (120–277V)  |  |                                   |                                  |
| ERP 0–10V, ELV, TRIAC<br>Dim-to-Dark <sup>8, 15</sup> |  | NXE NX Dual RJ45 SmartPORTS,<br>without Sensor <sup>15</sup>   |  |                                   |                                  |
|   |  | NXW NX Networked Wireless Radio Module<br>NXRM2 and Bluetooth Programming,<br>without Sensor <sup>15</sup> |  |                                   |                                  |

### TRIM

| NOR-2.5S                                 |  | TRM                          | Reflector Flange Color       |                  | Reflector Insert Color | Lens   |
|--|--|------------------------------|------------------------------|------------------|------------------------|--|
| Series                                   | Function   | Trim                         |                              |                  |                        |  |
| NOR-2.5S<br>Noni Recessed<br>2.5" Square | <b>Shallow Housing Compatible</b>  | TRM Trim                     | <b>Flanged</b>               |                  | <b>Texture</b>         | SOL Solite <sup>9</sup><br>CLR Clear <sup>9</sup><br>FRS Frosted <sup>10</sup><br>LIN Linear Spread<br>(10 x 40°) <sup>9, 11</sup><br>HEX Hexcel Louver <sup>9, 12</sup><br>NON No Lens <sup>9, 11</sup> |
|  | DS Downlight,<br>Shallow<br>( $\frac{5}{8}$ "–1 $\frac{1}{8}$ " ceiling) |                              | FWHS White                   | RWH White        |                        |  |
|  | DD Downlight, Deep<br>(1 $\frac{1}{4}$ " ceiling only)                   |                              | FGYS Gray                    | RGY Gray         |                        |  |
|  | LWS Lensed Wall Wash,<br>Shallow   |                              | FBLS Black                   | RBL Black        |                        |  |
|  | <b>Deep Housing Compatible</b>   |                              | FCOS Copper                  | RGT Graphite     |                        |  |
|  | LWD Lensed Wall Wash,<br>Deep  |                              | FAMW Anti-Microbial<br>White | RPP Pink Panache |                        |  |
|  | AA Adjustable Accent   |                              | FX Custom Finish             | RGH Grasshopper  |                        |  |
|  |  |                              | <b>Flush Mount</b>           |                  | <b>Smooth</b>          |  |
|  |  |                              | FT Flush Mount               | RWHS White       |                        |  |
|  |  |                              |                              | RGYS Gray        |                        |  |
|  |  | RBLS Black                   |                              |                  |                        |  |
|  |  | RCOS Copper                  |                              |                  |                        |  |
|  |  | RAMW Anti-Microbial<br>White |                              |                  |                        |  |
|  |  |                              | <b>Other</b>                 |                  |                        |  |
|  |  |                              | RX Custom Finish             |                  |                        |  |

- Notes:
- Available in 10 or 17 watt outputs
  - DL performance based on SOL lens with RWHS insert finish
  - Available only with FRS lens
  - Available only when LW functions selected
  - Not available with LVE control
  - Available only with DL and AA functions
  - Available with all functions. Must be selected with LWS and LWD
  - Available with DS only
  - HEX and NON suitable for damp location only
  - Above ceiling access required
  - Only available in 17 or 25 watt outputs
  - DM1 or ERP required with NX options