

NOR-3.5R

NONI 3.5" ROUND RECESSED FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOR-3.5RDL-NHN17-930K-MD-DM1NU / NOR-3.5RDS-TRM-FWHS-RBL-SOL

CATALOG #	
-----------	--

HOUSING

NOR-3.5R					
Series	Function	Housing	Output	CRI/CCT	Beam Spread ⁵
NOR-3.5R Noni Recessed 3.5" Round	Shallow Housing (2" Depth)	NHN New Construction, Non-IC NHI New Construction, IC ¹ CP Chicago Plenum ¹	10 10 Watt 17 17 Watt 25 25 Watt	Static 927K 90 CRI, 2700K 930K 90 CRI, 3000K 935K 90 CRI, 3500K 940K 90 CRI, 4000K 830K 80 CRI, 3000K 835K 80 CRI, 3500K Dynamic 1830DT 90 CRI, 1800K–3000K Dim-to-Warm ^{1,2,3} 2765T 90 CRI, 2700K–6500K SpectraSync™ Tunable White ^{1,2,3,4}	VN Very Narrow (.42 SC / 25°) NR Narrow (.50 SC / 30°) MD Medium (.58 SC / 35°) WD Wide (.80 SC / 50°) XW Extra Wide (1.06 SC / 75°) ⁶ LW Lensed Wall Wash ⁷
	DL Downlight				
	LWS Lensed Wall Wash, Shallow				
	Deep Housing (3" Depth)				
	LWD Lensed Wall Wash, Deep				
	AA Adjustable Accent				

		U	RMB
Dimming	Controls ¹³	Voltage	Accessories
DM1 0–10V 1% ^{8,14,15}	N None LV Lutron Vive 0–10V (120–277V) LVE Lutron Vive EcoSystem (120V Only) NXE NX Dual RJ45 SmartPORTS, without Sensor ¹⁵ NXW NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ¹⁵	U Universal Voltage (120–277V)	RMB Residential Mounting Bars
PDM ELV, TRIAC 1% ^{8,14}			
ERP 0–10V, ELV, TRIAC Dim-to-Dark ^{8,15}			
PEQ0E Lutron Hi-Lume Premier 0.1%			
SpectraSync			
DMT 0–10V 5% ⁴			

TRIM

NOR-3.5R		TRM			
Series	Function	Trim	Reflector Flange Color	Reflector Insert Color	Lens
NOR-3.5R Noni Recessed 3.5" Round	Shallow Housing Compatible	TRM Trim	Flanged FWHS White FGYS Gray FBLS Black FCOS Copper FAMW Anti-Microbial White FX Custom Finish Flangeless FT Flangeless	Texture RWH White RGY Gray RBL Black RGT Graphite RPP Pink Panache RGH Grasshopper Smooth RWHS White RGYS Gray RBLs Black RCOS Copper RAMW Anti-Microbial White Other RX Custom Finish	SOL Solite ⁹ CLR Clear ⁹ FRS Frosted ¹⁰ LIN Linear Spread (10 x 40°) ^{9,11} HEX Hexcel Louver ^{9,12} NON No Lens ^{9,11}
	DS Downlight, Shallow (¾"–1 ½" ceiling)				
	DD Downlight, Deep (1 ¼" ceiling only)				
	LWS Lensed Wall Wash, Shallow				
	Deep Housing Compatible				
	LWD Lensed Wall Wash, Deep				
	AA Adjustable Accent				

Notes:

- Available in 10 or 17 watt outputs
- NHN housing only
- Available with NR or LW optic only
- DMT driver must be selected for use with 2765T
- DL and AA performance based on SOL lens with RWHS insert finish
- Available only with FRS lens
- Available only when LW functions selected
- Not available with LVE control
- Not available with LW function
- Available with all functions. Must be selected with LW
- Available with DS only
- Wet location not suitable for HEX or NON
- Above ceiling access required
- Only available in 17 or 25 watt outputs
- DM1 or ERP required with NX options