

NOR-3.5S

NONI 3.5" SQUARE RECESSED FAMILY

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Examples: NOR-3.5SDL-NHN17-930K-MD-DM1NU/NOR-3.5SDS-TRM-FWHS-RBL-SOL

CATALOG #	
-----------	--

HOUSING

NOR-3.5S							
Series	Function	Housing	Output	CRI/CCT	Beam Spread ⁵		
NOR-3.5S Noni Recessed 3.5" Square	Shallow Housing (2" Depth)	NHN New Construction, Non-IC	10 10 Watt	Static 927K 90 CRI, 2700K 930K 90 CRI, 3000K 935K 90 CRI, 3500K 940K 90 CRI, 4000K 830K 80 CRI, 3000K 835K 80 CRI, 3500K Dynamic 1830DT 90 CRI, 1800K–3000K Dim-to-Warm ^{1,2,3} 2765T 90 CRI, 2700K–6500K SpectraSync™ Tunable White ^{1,2,3,4}	VN Very Narrow (.38 SC / 25°)		
	DL Downlight	NHI New Construction, IC ¹	17 17 Watt		NR Narrow (.48 SC / 30°)		
	LWS Lensed Wall Wash, Shallow	CP Chicago Plenum ¹	25 25 Watt		MD Medium (.58 SC / 35°)		
	Shallow Housing (3" Depth)				WD Wide (.84 SC / 50°)		
	LWD Lensed Wall Wash, Deep				SS Square in Square (.90 SC / 60°)		
	AA Adjustable Accent				LW Lensed Wall Wash ⁷		

		U		RMB	
Dimming	Controls ¹³	Voltage	Accessories		
DM1 0–10V 1% ^{8,14,15}	N None	U Universal Voltage (120–277V)	RMB Residential Mounting Bars		
PDM ELV, TRIAC 1% ^{8,14}	LV Lutron Vive 0–10V (120–277V)				
ERP 0–10V, ELV, TRIAC Dim-to-Dark ^{8,15}	LVE Lutron Vive EcoSystem (120V Only)				
PEQ0E Lutron Hi-Lume Premier 0.1%	NXE NX Dual RJ45 SmartPORTS, without Sensor ¹⁵				
SpectraSync	NXW NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor ¹⁵				
DMT 0–10V 5% ⁴					

TRIM

NOR 3.5S		TRM			
Series	Function	Trim	Reflector Flange Color	Reflector Insert Color	Lens
NOR-3.5S Noni Recessed 3.5" Square	Shallow Housing Compatible		Flanged	Texture	SOL Solite ⁹
	DS	Downlight, Shallow (¾"-1 ½" ceiling)	FWHS White	RWH White	CLR Clear ⁹
	DD	Downlight, Deep (1 ¼" ceiling only)	FGYS Gray	RGY Gray	FRS Frosted ¹⁰
	LWS	Lensed Wall Wash, Shallow	FBLS Black	RBL Black	LIN Linear Spread (10 x 40°) ^{9, 11}
			FCOS Copper	RGT Graphite	HEX Hexcel Louver ^{9, 12}
			FAMW Anti-Microbial White	RPP Pink Panache	NON No Lens ^{9, 11}
			FX Custom Finish	RGH Grasshopper	
			Smooth		
			RWHS White		
			RGYS Gray		
			RBLS Black		
			RCOS Copper		
			RAMW Anti-Microbial White		
				Other	
				RX Custom Finish	

- Notes:
- Available in 10 or 17 watt outputs
 - NHN available up to 17 watts. NHI available as 10 watts
 - Available with NR or LW optic only
 - DMT driver must be selected for use with 2765T
 - DL and AA performance based on SOL lens with RWHS insert finish
 - Available only with FRS lens
 - Available only when LW functions selected
 - Not available with LVE control
 - Not available with LW function
 - Available with all functions. Must be selected with LW
 - Available with DS only
 - Wet location not suitable for HEX or NON
 - Above ceiling access required
 - Only available in 17 or 25 watt outputs
 - DM1 or ERP required with NX options