

ORDERING GUIDE

Example: AIRA-W-SD-LPA-24-8-SOF-WHS-RGYS-35K9-SD050-D01-1C-UNV-WM

CATALOG # _____

AIRA	W						
Series	Mounting	Fixture Distribution	Indirect Optics	Row Length	Max Length in Row	Diffuser	Finish
AIRA	W Wall	SD Semi-Direct (25/75)	LPA Low Peak Angle	' Enter in foot increments	2 2' 3 3' 4 4' 5 5' 6 6' 8 8'	SOF Soft Diffuse Lens	WHS White, Smooth (C1) GYS Gray, Smooth (C4) BLS Black, Smooth (C5) CC Custom Color

Crossbar Insert Finish	CCT/CRI	Lumen Output ³	Dimming	Circuiting	Voltage	Mounting Kit
RWHS White, Smooth (C1)	27K9 2700K, 90CRI	SD015 150 (min) to SD150 1500 (max)	D01 1% 0–10V D05 5% 0–10V NDM Non-Dimming LEC 1% Lutron Hi-Lume EcoSystem ¹ DALIP DALIP ¹ SEN 1% for use with Sensors	1C Single Circuit	UNV Universal (120V-277V) 347 347V ^{1,4}	WM Wall Mount (ADA)
RGYS Gray, Smooth (C4)	30K9 3000K, 90CRI					
RBLS Black, Smooth (C5)	35K9 3500K, 90CRI					
RWH White, Textured	40K9 4000K, 90CRI					
RGY Gray, Textured	50K9 5000K, 90CRI					
RBL Black, Textured	2765T 2700–6500K Tunable White, 90CRI ^{1,2}					
RGT Graphite						
RPP Pink Panache						
RGH Grasshopper						
RCOS Copper						
RX Custom Color						

Emergency ⁵	Patterns ⁶	Controls & Sensors ^{1,7}
EF 10W Emergency Battery Pack (CEC Title 20 Compliant) Enter quantity. 2EF = 2 emergency batteries/row	C90IC 90° Inside Corner C90OC 90° Outside Corner	NX - Wired Networked ⁸ NXE NX Wired Dual RJ45 SmartPORTS, without Sensor

Notes:

- 1 Additional lead time may be applicable. Consult factory.
- 2 Must be ordered with D05 dimming.
- 3 Specifiable in 50 lumen increments. Reference the Performance Data Table for full performance offering and exceptions.
- 4 Compatible with D01, D05, NDM, SEN. Excludes EF option.
- 5 EF - 10W battery powered driver. Provides a minimum of 90 minutes of emergency lighting.
- 6 Submittal drawings required for use with EF or 2765T configurations.
- 7 Consult factory for wireless controls and sensor options.
- 8 Refer to NX Integrated Controls Reference Table for Functionality of Options.