

ORDERING GUIDE

Example: AIRA-W-SD-LPA-24-8-SOF-WHS-RGYS-35K9-SD050-D01-1C-UNV

CATALOG # _____

AIRA	W						
Series	Mounting	Fixture Distribution	Indirect Optics	Row Length	Max Length in Row	Diffuser	Finish
AIRA	W Wall	SD Semi-Direct (25/75)	LPA Low Peak Angle	' Enter in foot increments	2 2' 3 3' 4 4' 5 5' 6 6' 8 8'	SOF Soft Diffuse Lens	WHS White, Smooth (C1) GYS Gray, Smooth (C4) BLS Black, Smooth (C5) CC Custom Color

Crossbar Insert Finish	CCT/CRI	Lumen Output ⁸	Dimming	Circuiting	Voltage
RWHS White, Smooth (C1)	27K9 2700K, 90CRI	SD015 150 (min) to	D01 1% 0-10V	1C Single Circuit	UNV Universal (120V-277V)
RGYS Gray, Smooth (C4)	30K9 3000K, 90CRI	SD150 1500 (max)	D05 5% 0-10V		347 347V ^{1,4}
RBLS Black, Smooth (C5)	35K9 3500K, 90CRI		NDM Non-Dimming		
RWH White, Textured	40K9 4000K, 90CRI		LEC 1% Lutron Hi-Lume EcoSystem ¹		
RGY Gray, Textured	50K9 5000K, 90CRI		DALIP DALIP ¹		
RBL Black, Textured	2765T 2700-6500K Tunable White, 90CRI ^{1,2}		SEN 1% for use with Sensors		
RGT Graphite					
RPP Pink Panache					
RGH Grasshopper					
RCOS Copper					
RX Custom Color					

Emergency ⁵	Patterns ⁶	Controls & Sensors ^{1,7}
EF 10W Emergency Battery Pack (CEC Title 20 Compliant) Enter quantity. 2EF = 2 emergency batteries/row	C90IC 90° Inside Corner C90OC 90° Outside Corner	NX - Wired Networked ⁸ NXE NX Wired Dual RJ45 SmartPORTS, without Sensor

Notes:

- Additional lead time may be applicable. Consult factory.
- Must be ordered with D05 dimming.
- Specifiable in 50 lumen increments. Reference the Performance Data Table for full performance offering and exceptions.
- Compatible with D01, D05, NDM, SEN. Excludes EF option.
- EF - 10W battery powered driver. Provides a minimum of 90 minutes of emergency lighting.
- Submittal drawings required for use with EF or 2765T configurations.
- Consult factory for wireless controls and sensor options.
- Refer to NX Integrated Controls Reference Table for Functionality of Options.