

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Example: AIRA-SW-SD-LPA-24-8-SOF-WHS-35K9-SD100-D01-1C-UNV

CATALOG #

AIRA	SW						
Series	Mounting	Fixture Distribution	Indirect Optics	Row Length	Max Length in Row	Diffuser	Finish
AIRA	SW Sconce Wall	SD Semi-Direct (25/75)	LPA Low Peak Angle	____' Enter in foot increments	2 2' 3 3' 4 4' 5 5' 6 6' 8 8'	SOF Soft Diffuse Lens	WHS White, Smooth (C1) GYS Gray, Smooth (C4) BLS Black, Smooth (C5) CC Custom Color

End Cap Finish	CCT/CRI	Lumen Output ³	Dimming	Circuiting	Voltage
RWHS White, Smooth (C1)	27K9 2700K, 90CRI	SD015 150 (min)	D01 1% 0-10V	1C Single Circuit	UNV Universal (120V-277V)
RGYS Gray, Smooth (C4)	30K9 3000K, 90CRI	to	D05 5% 0-10V		347 347V ^{1,4}
RBLS Black, Smooth (C5)	35K9 3500K, 90CRI	SD100 1000 (max)	NDM Non-Dimming		
RWH White, Textured	40K9 4000K, 90CRI		LEC 1% Lutron Hi-Lume EcoSystem ¹		
RGY Gray, Textured	50K9 5000K, 90CRI		DALIP DALIP ¹		
RBL Black, Textured	2765T 2700-6500K Tunable White, 90CRI ^{1,2}		SEN 1% for use with Sensors ¹		
RGT Graphite					
RPP Pink Panache					
RGH Grasshopper					
RCOS Copper ¹					
RX Custom Color ¹					

OPTIONAL

Emergency ⁶	Patterns ^{1,6}
EF 10W Emergency Battery Pack (CEC Title 20 Compliant) Enter quantity. 2EF = 2 emergency batteries/row	C90IC 90° Inside Corner C90OC 90° Outsider Corner

Controls & Sensors ^{1,8}
NX Networked - Wireless ⁸
NXWSM NX Networked Wireless Enabled Integral NXSMP2-SMI PIR Occupancy Sensor with Automatic Dimming Photocell and Bluetooth Programming

Notes:

- Additional lead time may be applicable. Consult factory.
- Must be ordered with D05 dimming.
- Specifiable in 50 lumen increments. Reference the Performance Data Table for full performance offering and exceptions.
- Compatible with D01, D05, NDM, SEN. Excludes EF option.
- EF - 10W battery powered driver. Provides a minimum of 90 minutes of emergency lighting.
- Submittal drawings required for use with EF or 2765T configurations
- Consult factory for wireless controls and sensor options. Not available for row mounting. Not available in 2' or 3' lengths.
- Refer to NX Integrated Controls Reference Table for Functionality of Options. Minimum mounting height with Sensor is 7ft. Please reference coverage chart on page 3 for more information.