



LED Lamps - Plug-in



Type A 4-pin Plug-in Lamps

Current's Type A LED Plug-in lamps are direct replacements for pin-based compact fluorescent lamps. These lamps operate from CFL ballasts. Horizontal and vertical orientation lamps are offered in order to minimize energy consumption and improve fixture efficiency.

PERFORMANCE HIGHLIGHTS:

Type A 4-pin Plug-in Lamps	
Light Output Range:	1000-2200 Lumens
CRI:	80
Selectable CCT:	2700K, 3000K, 3500K & 4000K
Efficiency:	Up to 129 LPW
Wattage:	9W - 18.5W
Life:	50,000 hours L70
Temperature Rating:	-20°C to 45°C
Location Rating:	Damp

LIMITED WARRANTY

5 years

FEATURES:

- Lasts 2.5X longer than CFL
- 50,000 hours rated life (L70)
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS
- SpectraChoice™ Selectable Type A Plug-in offers built-in switch with four color temperature options

BENEFITS:

Energy + Cost Savings

- Uses 50% less energy than CFL
- 9W LED saves over \$93 in energy vs 26 watt CFL
- 18.5W LED saves over \$129 in energy vs 42 watt CFL
- Energy savings based on \$0.11 per kWh over the rated life of the lamp.
- Directional optics eliminate wasted light to deliver lumens more efficiently
- Long life means fewer lamp replacements versus compact fluorescent light sources.
- Reduce inventory with SpectraChoice™ Type A Plug-in

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.



LED Lamps - Plug-in

Type A 4-pin Plug-in Lamps

CUSTOMER NAME _____

PROJECT NAME _____


DATE _____

NOTES _____

Selectable SpectraChoice™ Type A - 4-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Carton Qty ²	MOL (In)	Lumens (Initial) ⁵	Color Temp* (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	DLC ⁴	Location Rating ³	Additional Information [*]
Vertical Type A 4-pin														
Plug-In	G24q/GX24q	9	93300089	LED9G24q-V/8SC-4PK	24	5.9	1000 1100 1100 1100	2700K 3000K 3500K 4000K	80	13/18/26	50,000	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast, Fully Enclosed, 4 pack

Type A - 4-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Carton Qty²	MOL (In)	Lumens (Initial)³	Color Temp* (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs)¹	DLC⁴	Location Rating²	Additional Information⁵	
Vertical Type A 4-pin															
	Plug-In	G24q/GX24q	9	33969	LED9G24q-V/830	6	5.9	1200	3000K	80	13/18/26	50,000	-	Damp	Requires Electronic Ballast, Fully Enclosed
		GX24q	18.5	39288	LED19GX24q-V/827	6	6.42	1800	2700K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39277	LED19GX24q-V/830	6	6.42	1850	3000K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39275	LED19GX24q-V/835	6	6.42	1950	3500K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39279	LED19GX24q-V/840	6	6.42	1950	4000K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
Horizontal Type A 4-pin															
	Plug-In	G24q/GX24q	9	33994	LED9G24q-H/827	6	5.31	1100	2700K	80	13/18/26	50,000	-	Damp	Requires Electronic Ballast, Fully Enclosed
		G24q/GX24q	9	33997	LED9G24q-H/830	6	5.31	1200	3000K	80	13/18/26	50,000	-	Damp	Requires Electronic Ballast, Fully Enclosed
		G24q/GX24q	9	33998	LED9G24q-H/835	6	5.31	1200	3500K	80	13/18/26	50,000	-	Damp	Requires Electronic Ballast, Fully Enclosed
		G24q/GX24q	9	33999	LED9G24q-H/840	6	5.31	1200	4000K	80	13/18/26	50,000	-	Damp	Requires Electronic Ballast, Fully Enclosed
		GX24q	18.5	39289	LED19GX24q-H/827	6	6.7	1850	2700K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39282	LED19GX24q-H/830	6	6.7	1850	3000K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39276	LED19GX24q-H/835	6	6.7	1950	3500K	80	32/42	50,000	-	Damp	Requires Electronic Ballast
		GX24q	18.5	39283	LED19GX24q-H/840	6	6.7	1950	4000K	80	32/42	50,000	-	Damp	Requires Electronic Ballast

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

⁴ Not all product variations on this page are DLC qualified. Visit qpl.designlights.org/solid-state-lighting to confirm qualification.

⁵ Lumen levels correspond with color temperature for selectable lamps

* Default color temperature setting is 4000K for selectable lamps

* Check ballast compatibility at LED.com/LED4pin-compatibility for G24q/GX24q lamps

Approximate performance when replacing listed CFL Plug-In lamps with a Current LED Plug-In

Original 4-Pin CFL Plug-In (DBX, TBX) Performance		Subsequent performance when replaced a 9W 4-Pin LED Plug-In (DBX, TBX)		Subsequent performance when replaced a 18.5W 4-Pin LED Plug-In (TBX)	
Watts	Approximate Lumens	Watts	Approximate Lumens	Watts	Approximate Lumens
13	900	5	750	-	-
18	1200	6.5	900	-	-
26	1800	9	1200	-	-
32	2400	9	1200	16	1700
42	3200	-	-	11	1800

