

LED Lamps - Directional



SpectraChoice™ RS Can Downlights

Current's SpectraChoice™ Selectable RS Can Downlights are the perfect solution to give an updated look to ceilings with recessed lighting. Make color temperature selections easily at any time with integrated switch, no tools required.



PERFORMANCE HIGHLIGHTS:

Selectable RS Cans

Light Output Range: 700 (4"), 700 & 1100 (6") Lumens

CRI: 90

Selectable CCT: 2700K, 3000K, 4000K & 5000K

Input Voltage: 120

Efficiency: Up to 91 LPW

Wattage: 8W (4"), 8W & 12W (6")

Life: 50,000 hours L70

Temperature Rating: -20°C to 40°C

Location Rating: Damp

LIMITED WARRANTY

5 years



Select color temperature using built-in switch.

FEATURES:

- Select color temperature with built-in switch, no tool required
- CEC itle 24-JA8 compliant
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

BENEFITS:

- For example, a replacement lamp using 8 watts of energy and producing 700 lumens can save over \$313 in energy costs over the rated life of the lamp vs. a standard 700 lumen, 65-watt incandescent BR30 based on \$0.11 per kWh
- Use the integrated switch to match the color of lighting across the facility or choose to change the aesthetic of a space
- One lamp can replace many, greatly reducing inventory
- Use one lamp for applications requiring different CCTs, simplifying project management by streamlining BOMs

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.



Do more with less.

- Reduce Inventory
- Simplify Projects
- Optimize Solutions





LED Lamps - Directional

SpectraChoice™ RS Can Downlights

CUSTOMER NAME			
PROJECT NAME			
DATE	NOTES		

Selectable SpectraChoice™ RS Cans

Bulb Shape	Base Type		Order Code	Description	Volts		MOL (ln)	Lumens (Initial)	Selectable Color Temperature*	CRI		Rated Life			Location Rating ³	Additional Information
Selectab	le RS C	ans														
}	E26	8	93162554	LED8DRS4/9SC-4PK	120	16	2.4	700	2700/3000/4000/5000K	90	65	50,000	Yes	*	Damp	4" Can, Pigtail, Title 24-JA8, 4 pack
2	E26	8	93162555	LED8DRS6/9SC-4PK	120	16	2.8	700	2700/3000/4000/5000K	90	65	50,000	Yes	*	Damp	6" Can, Pigtail, Title 24-JA8, 4 pack
	E26	12	93162556	LED12DRS6/9SC-4PK	120	16	2.8	1100	2700/3000/4000/5000K	90	90	50,000	Yes	*	Damp	6" Can, Pigtail, Title 24-JA8, 4 pack


Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.


^{*} Default color temperature setting is 3000K.




E26 base pigtail with quick disconnect and mounting clips included.

Optional torsion springs provided with 6-inch models.







Go to www.LED.com to learn more about Current's family of Selectable LED Lamps.





¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity from Current = Carton Qty; Smaller unit of sale pack inside carton

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations
Dry Location – Location not normally subject to dampness, may include a location subject to temporary dampness (i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture)
Wet Location – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

[★] ENERGY STAR® status: ENERGY STAR® certified. Lamps without a "★" are not ENERGY STAR® certified.