



LED Lamps - Plug-in



SpectraChoice™ Type A 4-pin Plug-in

SpectraChoice™ Type A Plug-in lamps with Selectable CCT provide an easy solution to leverage the low energy and long life of LED. Simply plug the LED lamp into the existing fixture, no tools or re-wiring required.



SpectraChoice™

PERFORMANCE HIGHLIGHTS:


SpectraChoice™ Type A 4-pin Plug-in Lamp	
Light Output Range:	1000-1100 Lumens
CRI:	80
Selectable CCT:	2700K, 3000K, 3500K & 4000K
Efficiency:	Up to 122 LPW
Wattage:	9W
Life:	50,000 hours L70
Temperature Rating:	-20°C to 40°C
Location Rating:	Damp

LIMITED WARRANTY

5 years



SpectraChoice™



Select color temperature using built-in switch.

FEATURES:

- Select color temperature with built-in switch, no tool required
- Fits in 4-pin G24q sockets
- Operates from electronic ballasts
- Directional light output for improved fixture efficiency
- Lasts 2.5x longer than CFL
- These lamps are energy efficient, contain no lead or mercury and are compliant with material restriction requirements of RoHS

BENEFITS:

- For example, using only 9 watts of energy, save over \$90 in energy costs over the rated life of the lamp versus a standard 26-watt compact fluorescent lamp based on \$0.11 per kWh
- One lamp can replace many, greatly reducing inventory
- Use one lamp for applications requiring different CCTs, simplifying project management by streamlining BOMs
- Match color temperature across space with flip of a switch

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.



Selectable LED Lamps

Do more with less.

- Reduce Inventory
- Simplify Projects
- Optimize Solutions



LED Lamps - Plug in

SpectraChoice™ Type A 4-pin Plug-in

CUSTOMER NAME _____

PROJECT NAME _____

DATE _____

NOTES _____

Selectable SpectraChoice™ Type A - 4-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Carton Qty ²	MOL (In)	Lumens (Initial) ⁵	Color Temp* (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) ¹	DLC ⁴	Location Rating ³	Additional Information ⁶
Vertical Type A 4-pin														
Plug-In	G24q/GX24q	9	93300089	LED9G24q-V/8SC-4PK	24	5.9	1000 1100 1100 1100	2700K 3000K 3500K 4000K	80	13/18/26	50,000	Yes	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast, Fully Enclosed, 4 pack

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations


⁴ Not all product variations on this page are DLC qualified. Visit qpl.designlights.org/solid-state-lighting to confirm qualification.

⁵ Lumen levels correspond with color temperature for selectable lamps

* Default color temperature setting is 4000K for selectable lamps


⁶ Check ballast compatibility at LED.com/LED4pin-compatibility

LED G24q 4-pin Base




**Works in 4-pin
G24q/GX24q
Sockets**

Compact Fluorescent G24q 4-pin Bases



Compact Fluorescent GX24q 4-pin Bases



Vertical Configuration

