


LNC
COMPACT LED LITEPAK

FEATURES

- Compact LNC LED is designed for perimeter illumination and available in 3 lumen packages for safety, security and identity
- 3000K, 4000K, 5000K and Amber color temperatures
- Up to 4:1 spacing to mounting height ratio means fewer fixtures to install
- Acrylic diffuser included! Use for applications near entrances or locations where reduced brightness is desired. (Maximum spacing with diffuser 30ft)
- Die-cast aluminum housing with decorative Laredo styling
- Full cut-off neighbor friendly
- Listed to UL1598 for use in wet locations



SPECIFICATIONS

CONSTRUCTION

- Decorative die-cast aluminum housing and door
- Rugged design protects internal components and provides excellent thermal management for long life
- Powder paint finishes provide lasting appearance in outdoor environments
- Full cut-off distribution; Ambient diffuser included, use for applications near entrances or locations where reduced brightness is desired

OPTICS

- Drivers are 120-277V, 50/60Hz Type II, III and Type IV lenses provide wide lateral spread
- 3000K - 80 CRI, 4000K - 70 CRI, and 5000K - 70 CRI, CCT nominal
- Drivers have greater than .90 power factor and less than 20% Total Harmonic Distortion

INSTALLATION

- Quick mount adapter provides quick installation, designed for recessed box 4" square junction box

ELECTRICAL

- 60,000 hours minimum LED life at L96 rating per IESNA TM-21-11
- Minimum operating temperature is -40°C/-40°F
- 0-10V dimming 120-277V only
- LNC5L – 5 LEDs, Types II, III or IV available, see page 2 for electrical details
- LNC7L – 7 LEDs, Type II, III or IV available, see page 2 for electrical details
- LNC9L – 9 LEDs, Types II, III or IV available, see page 2 for electrical details

CONTROLS

- Photocontrol option is available to provide dusk-to-dawn control for additional energy savings

CERTIFICATIONS

- Listed and labeled to UL 1598 for wet locations, 25°C ambient environments

WARRANTY

- 5 year warranty

KEY DATA	
Lumen Range	800–2100
Wattage Range	13–22
Efficacy Range (LPW)	64–95
Fixture Projected Life (Hours)	L96>60K
Weights lbs. (kg)	9.6 (24.5)

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Example: LNC-5L-U-3K-2-BLT-PCU

CATALOG #

ORDERING INFORMATION

Series	# LEDs	IES Distribution	Voltage	CCT/CRI	Finish	Controls
LNC LNC Zero Uplight	5L 5 LEDs	2 Type II	U 120-277V	3K 3000K nominal, 70 CRI	BLT Black Matte Textured	PCU Universal Button Photocell
	7L 7 LEDs	3 Type III	1 120V	4K 4000K nominal, 70 CRI	BLS Black Gloss Smooth	
	9L 9 LEDs	4 Type IV	2 208V 3 240V 4 277V	5K 5000K nominal, 70 CRI AM Amber (590 μm available for "Turtle Friendly"/ observatory applications, 350mA (consult factory) ¹)	DBT Dark Bronze Matte Textured DBS Dark Bronze Gloss Smooth GTT Graphite Matte Textured LGS Light Grey Gloss Smooth PSS Platinum Silver Smooth WHT White Matte Textured WHS White Gloss Smooth VGT Verde Green Textured	
					Color Option	
					CC Custom Color	

Notes:
1 Amber LEDs only available on 7L and 9L configurations, 350mA

REPLACEMENT PARTS AND ACCESSORIES

Catalog Number	Description
<input type="checkbox"/> 93039574	Frosted comfort shield, improved uniformity with only 5% reduction

PERFORMANCE DATA

# Of LEDs	Nominal Wattage	System Watts	Dist. Type	5K (5000K NOMINAL 70 CRI)		4K (4000K NOMINAL 70 CRI)		3K (3000K NOMINAL 80 CRI)		AM (<580 nm wave-length)		
				Lumens	LPW*	Lumens	LPW	Lumens	LPW	Lumens	System Watts	LPW*
5	STD. (700mA) AM (350mA)	13W	2	1,150	88.5	1,052	81	883	68	-	-	-
			3	1,132	87	1,077	83	833	64	-	-	-
			4	1,146	88	1,053	81	849	65	-	-	-
7		17W	2	1,515	89	1,369	80.5	1,272	75	-	-	-
			3	1,500	88	1,539	90.5	1,392	82	268	6.6	59
			4	1,557	91.5	1,535	90	1,425	84	-	-	-
9	22W	2	2,069	94	2,033	92	1,588	72	-	-	-	
		3	2,024	92	1,989	90	1,623	74	-	-	-	
		4	2,095	95	2,059	93.5	1,680	76	382	8.3	46	

* Lumen values are from photometric tests performed in accordance with IESNA LM-79-08. Data is considered to be representative of the configurations shown. Actual performance may differ as a result of end-user environment and application. Please consult IES files for BUG ratings.

PROJECTED LUMEN MAINTENANCE

Ambient Temperature	OPERATING HOURS					
	0	25,000	50,000	TM-21-11* L96 60,000	100,000	L70 (Hours)
25°C / 77°F	1.00	0.97	0.97	0.96	0.95	>791,000
40°C / 104°F	0.99	0.96	0.96	0.96	0.94	>635,000

* Projected per IESNA TM-21-11* Data references the extrapolated performance projections for the LNC-12LU-5K base model in a 40°C ambient, based on 10,000 hours of LED testing per IESNA LM-80-08

LNC
COMPACT LED LITEPAK

ELECTRICAL DATA

# OF LEDS	Drive Current (mA)	Input Voltage (V)	Oper. Current (Amps)	System Power (W)
9	STD. (700mA)	120	0.11	13
		277	0.05	
12	STD. (700mA)	120	0.14	17
		277	0.07	
12	STD. (700mA)	120	0.17	22
		277	0.09	


LUMINAIRE AMBIENT TEMPERATURE FACTOR (LATF)

Ambient Temperature		Lumen Multiplier
0° C	32° F	1.02
10° C	50° F	1.01
20° C	68° F	1.00
25° C	77° F	1.00
30° C	86° F	1.00
40° C	104° F	0.99
50° C	122° F	0.98


Use these factors to determine relative lumen output for average ambient temperatures from 0-50°C (32-122°F).

PHOTOMETRY


LNC9LU – Type II




LNC9LU – Type III



LNC9LU – Type IV



DIMENSIONS



A	B	C	D
4.81" (122 mm)	1.55" (39 mm)	8.22" (209 mm)	5.25" (133 mm)

ADDITIONAL INFORMATION

SHIPPING INFORMATION

Catalog Number	G.W(kg)/CTN	Carton Dimensions			Carton Qty. per Master Pack
		Length Inch (cm)	Width Inch (cm)	Height Inch (cm)	
LNC-5LU	9.6 (4.36)	14.5 (37)	9.6 (24.5)	6.8 (17.5)	2
LNC-7LU	9.6 (4.36)	14.5 (37)	9.6 (24.5)	6.8 (17.5)	2
LNC-9LU	9.6 (4.36)	14.5 (37)	9.6 (24.5)	6.8 (17.5)	2

USE OF TRADEMARKS AND TRADE NAMES

All product and company names, logos and product identifies are trademarks™ or registered trademarks® of Current or their respective owners. Use of them does not necessarily imply any affiliation with or endorsement by such respective owners.