

LTR-6RW-RFH Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

LITEISTRY™

FEATURES

- 6" architectural LED wall wash delivering 600-2500 lm
- Single and double wall wash solutions
- Provides uniform vertical illumination as well as room side light
- Quiet reflector appearance with 50° optical cutoff
- SpectraSync™ Color Tuning technology allows the flexibility to tailor CCT to aesthetic preferences
- Available in Dim to Warm (2200K-3000K) or Tunable White (2700K-5000K or 2700K-6500K), 90+ CRI
- Available in Retrofit (non-IC) applications
- Standard with 0-10V dimming to 5%



CONTROL TECHNOLOGY



SPECIFICATIONS

CONSTRUCTION

- Die cast aluminum mounting ring with 5 axis adjustable junction box
- Retrofit housing allows below ceiling installation without removing the existing fixture
- Pre-wired junction box with snap-on covers for easy access
- Snap-in connection from driver compartment allows easy installation
- Light Engine connections use plenum rated (CMP) cable

OPTICS

- Visually pleasing 50° cutoff to source and source image
- Open cone and kicker reflector assembly with an optical grade silicone lens integral to light engine
- Available in Single and Double wall wash distributions
- Provides excellent uniformity down the wall while also contributing to room side lighting
- The light distribution is free of distracting bright spots or pixelation and the perimeter has a smooth transition
- High purity spun aluminum reflector, self-flanged
- Large selection of anodized finishes and colors
- Painted cones and flange options available

ELECTRICAL

- LED array with 3 SDCM color consistency
- Dim to Warm (2200K-3000K) or Tunable White (2700K-5000K or 2700K-6500K) options available
- 90+ CRI standard
- Long LED life: L70 at > 60,000 hours (TM-21)
- Universal voltage 120V-277V driver
- UL Class 2, inherent short circuit and overload protection
- Flicker free 0-10V dimming to 5%
- Refer to additional spec sheets for information on standard LITEISTRY solutions

INSTALLATION

- Accommodates ceiling thickness up to 2"
- Light engine/driver fully serviceable from above or below the ceiling

CERTIFICATIONS

- cCSAus certified to UL 1598
- Suitable for damp locations
- Approved for 8 (4 in/4 out) No. 12AWG conductors rated for 90°C through wiring
- This product qualifies as a "designated country construction material" per FAR 52.225-11 Buy American-Construction. Materials under Trade Agreements effective 6/6/2020.

WARRANTY

- 5 year warranty

KEY DATA	
Lumen Range	600-2500
Wattage Range	10-38
Efficacy Range (LPW)	57*
Reported Life (Hours)	L70 / >60,000
Input Current (mA)	83-317 (120V)

*Based on Specular, 30K, 90 CRI

LTR-6RW-RFH

Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ORDERING GUIDE

Example: LTR-6RD-RFH-SL10L-DMTW-LTR-6RW-T-SL2230TD9WW-S

CATALOG #	
-----------	--

HOUSING

LTR-6RD-RFH							
Aperture/Shape/Function		Lumen Package		Lumen Output		Driver Options	
LTR-6RD-RFH	6" Round Downlight/ WW/ DWW Wall Wash Retrofit Housing ³	SL	Standard Lumen	06L	600	DMTW	SpectraSync™ Dim to Warm, 0-10V Dimming to 5% ¹
				10L	1000		
		ML	Medium Lumen	15L	1500		
LTR-6RD-RFHW	6" Round Downlight/ WW/DWW Wall Wash Retrofit Housing ³	HL	High Lumen	20L	2000		
				25L	2500		
						Voltage	
						Housing Options	
						Standard 120-277V	
						F Fuse	

TRIM

LTR-6RW-T							
Aperture/Shape/Function		Lumen Package		CCT		CRI	
LTR-6RW-T	6" Round Wall Wash Light Engine/Trim Assembly	SL	Standard Lumen	2230TD	2200K-3000K SpectraSync™ Dim to Warm	9	90+CRI
		ML	Medium Lumen	2750T	2700K-5000K SpectraSync™ Tunable White		
		HL	High Lumen	2765T	2700K-6500K SpectraSync™ Tunable White		
						Distribution	
						WW Single Wall Wash	
						DWW Double Wall Wash	

TRIM CONTINUED

Reflector Finish		Reflector Color		Flange Color Options		Lower Trim Options		Reflector Options	
<i>Finish not applicable with painted reflectors (WC or BC)</i>		<i>Standard Clear</i>		<i>Standard matches reflector color</i>		WF Wide Flange		AM Antimicrobial Coating ³	
S	Specular	CG	Champagne Gold	WT	White Flange ⁴				
SS	Semi-Specular	BL	Black	BT	Black Flange ⁴				
MFC	American Matte™	LW	Light Wheat						
VS	Softglow®	PW	Pewter						
VSS	SoftSheen™	WC	Painted White Cone and Flange						
		BC	Painted Black Cone and Flange						

Accessories

- ☐ LiteGear LiteGear® Inverter, 125VA-250VA
- ☐ LPS Series LightPower Micro-Inverter, 20VA-55VA
- ☐ MOR6-R-WH Metal Oversized Ring, 6" Round, White (10" outside diameter)
- ☐ MOR6-R-BL Metal Oversized Ring, 6" Round, Black (10" outside diameter)

Notes:

- 1 Must select 2230TD with DMTW driver.
- 2 Must select either 2750T or 2765T with DMT driver.
- 3 See line art for compatibility with existing aperture diameters.
- 4 WT not needed for WC, BT not needed for BC.

LTR-6RW-RFH

Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

CONTROLS

SpectraSync™ Color Tuning Technology:


Control your space based on the needs of the application, specific activities throughout the day and preferences of the occupants with distinct SpectraSync™ Color Tuning Technologies.



SPECTRASync COLOR TUNING TECHNOLOGY		
Mode	Kelvin Range	Description
Dim to Warm	2200K-3000K	Mimics the familiar warming effect that occurs with traditional incandescent sources as they are dimmed
Tunable White	2700K-5000K 2700K-6500K	Offers users the ability to tailor CCT to their personal preference, enhancing task visibility, material and colors or the aesthetics of the space
Scheduled White	2700K-5000K 2700K-6500K	Mimics the rhythm of natural light or follows an alternative user-defined schedule throughout the day, enhancing an occupant's mood and well-being

SpectraSync Tunable White

Available in two options: 2750T (2700K–5000K) or 2765T (2700K–6500K).
Requires two 0–10V controllers, one for intensity and one for CCT.
Minimum 5% dimming.




SpectraSync Tunable White luminaires are provided with two 0–10V circuits. The violet and pink circuit is for wiring to any qualified 0–10V controller for dimming. The violet/white and pink/white circuit is for wiring to any qualified 0–10V controller for Tunable White CCT control.

Controller Manufacturer Data

SpectraSync Tunable White was designed to be used with sinking style dimmers (provided by others) and is compatible with:

- Current: NX Lighting Controls Room Controllers (NXRC) and In-fixture Controllers (NXFM)
- Lutron: DDTV, DVSTV, and NDTV dimmers
- Wattstopper: ADF120277 and CD4BL (Titan) dimmers




To enable scheduling and for use with NX wall control preset stations please refer to SpectraSync technical sheet.

LTR-6RW-RFH

Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

DIMENSIONS



Housing Compatibility Guide			
Existing Frame Opening**		Use Housing	Use Flange Option
MIN	MAX		
6.25" (156.3mm)	6.50" (165.1mm)	-RFH	(Standard)
6.63" (168.4mm)	6.88" (172.0mm)	-RFHW	WF

Dimensional Data		
Aperture	Standard	5.75" (146.1mm)
	Wide (WF)	7.75" (196.9mm)
Flange:	Standard	7.00" (177.8mm)
Ceiling Cutout:	Standard	6.50" (165.1mm)
Ceiling Thickness:	0.50" to 2.00" (12.7mm to 50.8mm)	

Lumen Package	"A"
06L-10L	5.90" (149.9mm)
15L-20L	7.86" (199.6mm)
25L	9.04" (229.6mm)

LTR-6RD-RFH/-RFHW

LTR-6RW-RFH

Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
 (WW/DWW) WITH COLOR TUNING

PHOTOMETRY

LTR-6RD-RFH-ML20L-DMTW / LTR-6RW-T-ML2230TD9WWS


LUMINAIRE DATA

Test No.	R19.00862-C20
Description	Single Wall Wash, 2000 lm, 3000K, 90 CRI
Delivered Lumens	2017
Watts	35.3W
Efficacy	57.0
Mounting	Recessed

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-40	1680	83.3
0-60	2015	96.9
0-90	2017	100.0
0-180	2017	100.0

POLAR GRAPH



CANDELA DISTRIBUTION

Degree	Candela
0	1620
5	1495
15	1243
25	1150
35	755
45	474
55	341
65	193
75	57
85	6
90	0

LUMINANCE DATA*

Vertical Angle	Average
45°	40013
55°	35478
65°	27294
75°	13034
85°	4370

*Candela/Square Meter

LTR-6RW-RFH


Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

TM-30 DATA

SPECTRASYNCTM TUNABLE WHITE (2765T)


COLOR VECTOR GRAPHIC
2700K, 90+ CRI



COLOR DISTORTION GRAPHIC
2700K, 90+ CRI




COLOR VECTOR GRAPHIC
4600K, 90+ CRI



COLOR DISTORTION GRAPHIC
4600K, 90+ CRI



COLOR VECTOR GRAPHIC
6500K, 90+ CRI



COLOR DISTORTION GRAPHIC
6500K, 90+ CRI



TEST RESULTS - TUNABLE WHITE @ 1500 LUMENS (NOMINAL)			
Value	2700K	4600K	6500K
Luminous Flux (lm)	1407	1604	1660
Wattage (W)	23.9	24.3	24.6
Efficacy (lm/W)	59	66	68
R _f	90	89	87
R _g	97	98	96
CCT (K)	2817	4588	6518
D _{uv}	-0.0013	-0.0040	0.0018
x	0.4482	0.3565	0.3131
y	0.4047	0.3531	0.3273
CIE R _a	91	95	94
CIE R _g	47	81	76

LTR-6RW-RFH


Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

TM-30 DATA CONTINUED


SPECTRASYNCTM DIM TO WARM (2230TD)

COLOR VECTOR GRAPHIC
3000K, 90+ CRI @ 100%




— Reference Illuminant — Test Source

COLOR DISTORTION GRAPHIC
3000K, 90+ CRI @ 100%




COLOR VECTOR GRAPHIC
2600K, 90 CRI @ 50% DIM




— Reference Illuminant — Test Source

COLOR DISTORTION GRAPHIC
2600K, 90 CRI @ 50% DIM




COLOR VECTOR GRAPHIC
2200K, 90 CRI @ 5% DIM



— Reference Illuminant — Test Source

COLOR DISTORTION GRAPHIC
2200K, 90 CRI @ 5% DIM



TEST RESULTS - DIM TO WARM @ 3 DIMMING LEVELS			
Value	100%	50% Dim	5% Dim
Luminous Flux (lm)	1501	772	53
Wattage (W)	24.3	14	3.4
Efficacy (lm/W)	62	55	16
R _f	90	92	91
R _g	97	99	102
CCT (K)	3123	2590	2282
D _{uv}	-0.0017	-0.0015	-0.0029
x	0.4261	0.4662	0.4907
y	0.3965	0.4082	0.4068
CIE R _a	92	93	93
CIE R _g	53	60	64

LTR-6RW-RFH Open SpectraSync

LITEISTRY 6" ROUND OPEN WALL WASH
(WW/DWW) WITH COLOR TUNING

ELECTRICAL DATA

DRIVER DATA	
Input Voltage	120-277 V
Input Frequency	50/60 Hz
Power Factor	≥0.90
THD	<20%
EMI Filtering (FCC 47 CFR Part 15)	Class A

ADDITIONAL INFORMATION

Central Inverters

For full fixture output in back-up mode, we recommend you visit currentlighting.com/dual-lite for your Central Lighting Inverter options. Please contact your local Current representative for any assistance with proper sizing and loading of your inverter selection. Central lighting inverters must be ordered separately.

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	