

# PURSUIT

## FEATURES

- Sections can be joined for runs up to 150' with seamless lens
- Electrical Connections IP68 rated
- Symmetric, Asymmetric, Wall Graze & Wall Wash Distributions
- "L", "T" & "X" Illuminated connectors for custom shapes
- Output up to 1,000 lm/ft in each direction
- Fixed arm, adjustable arm, pendant, wall & mullion mounting options



## ORDERING GUIDE

Example: RNLTX-L-ID-5-3K8-DL-UNV-BLT

CATALOG #




## HOUSING

| RNLTX   |   |                   |                    |                             |              |   |  |  |  |  |  |
|---|---|-------------------|--------------------|-----------------------------|--------------|---|--|--|--|--|--|
| Housing                                       | Light Engine                                    | Lumen Output      | CCT/CRI            | Shielding                   | Voltage      | Finish  |  |  |  |  |  |
| RNLTX-L Pursuit L shape illuminated connector | D Direct (Down)                                 | 5 500 lumens/ft   | 3K8 3000K, 80 CRI  | DL Diffuse lens - Down Only | UNV 120-277V | <b>BLS</b> Black Gloss Smooth<br><b>BLT</b> Black Matte Textured<br><b>DBS</b> Dark Bronze Gloss Smooth<br><b>DBT</b> Dark Bronze Matte Textured<br><b>GTT</b> Graphite Matte Textured<br><b>LGS</b> Light Grey Gloss Smooth<br><b>LGT</b> Light Grey Matte Textured<br><b>PSS</b> Platinum Silver Gloss Smooth<br><b>VGT</b> Verde Green Matte Textured<br><b>WHS</b> White Gloss Smooth<br><b>WHT</b> White Matte Textured<br><b>Color Option</b><br><b>CC<sup>2</sup></b> Custom Color |  |  |  |  |  |
|   | ID <sup>1</sup> Bidirectional (Up & Down Light) | 7 750 lumens/ft   | 3K9 3000K, 90 CRI  | CL Clear lens               |              |   |  |  |  |  |  |
| RNLTX-T Pursuit T shape illuminated connector | I <sup>1</sup> Indirect (Up Light)              | 10 1000 lumens/ft | 35K8 3500K, 80 CRI |                             |              |   |  |  |  |  |  |
|   |   |                   | 4K8 4000K, 80 CRI  |                             |              |   |  |  |  |  |  |
| RNLTX-X Pursuit X shape illuminated connector |   |                   | 4K9 4000K, 90 CRI  |                             |              |   |  |  |  |  |  |
|   |   |                   | 5K8 5000K, 80 CRI  |                             |              |   |  |  |  |  |  |




## ACCESSORIES

### Illuminated Connectors (Enables Custom Shapes)

RNLTX-L L shape  
RNLTX-T T shape  
RNLTX-XX shape



Connectors for the RND, Bidirectional (Up and Down) and RNI (Up)



Connectors for the RND, Direct (Down)

<sup>1</sup> The top of the connectors are not lit. Both sides connects are not lit for the up configuration.

<sup>2</sup> Consult factory for custom color, marine and corrosive finish options.