

PGL8

FEATURES

- Patent pending edge-lit, drop lens optic
- The PGL8 offers exceptional uniformity and visual comfort with four standard distribution patterns
- Multiple control options available for an intelligent parking garage lighting solution
- Integral sensors, battery backup and uplight



PGL8, Type V Concentrated



CONTROL TECHNOLOGY



RELATED PRODUCTS

Ouro

Pavilion

PGL7

SPECIFICATIONS

CONSTRUCTION

- Two-piece low copper aluminum alloy die-cast housings with internal cooling fins
- Molded silicone gaskets throughout ensure the sealing between the two compartments and provides ingress protection
- Housing is designed with integral LED heat sink utilized for thermal transfer
- Electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powder coated for fade and abrasion resistant
- Standard lens is one-piece injection molded acrylic, .09" minimum wall thickness. Perimeter is fully sealed with a one-piece molded silicone gasket, sealing the lens to the lens frame and electrical housing, for IP66 fixture rating

OPTICS

- Patent pending edge-lit, drop lens provides non-pixelated light for unprecedented visual comfort
- Four standard distributions: Type 5 Square, Type 5 Concentrated, Type 5 Rectangular and Type 4 Asymmetric

INSTALLATION

- Speed mount electro-zinc plated steel for mounting to standard 4" junction box or mud-box. Fixture hangs from hook to free both hands to make field wire connections. Allows tool-free fixture mounting to junction box, with integral anti-theft lock
- Direction arrow on mounting plate points in the direction of travel along the drive lane to insure luminaire is installed in the correct orientation

INSTALLATION (CONTINUED)

- Balanced pendant j-box and bird shroud are die-cast aluminum, pendant entry to balance fixture in free-swinging installation. Conduit pipe provided by others. The Kim Speed Mount is furnished for fixture attachment to the PB2. This option is shipped separate from fixture

ELECTRICAL

- 120V through 480V @ 50/60Hz
- Power Factor = >.90
- National Electrical Code, ANSI/NFPA 70
- 20kV surge suppression
- Thermal shield, dynamic thermal control
- -40°C starting driver
- 0–10V dimming interface
- Electronic components are UL and/or CSA listed
- 10% to 100% dimming by the use of standard 0–10V interface driver
- To activate the dimming system, a wiring harness is supplied and attached to the DIM Port (DIM IN) on the thermal shield protection system. This port allows the 0–10V interface to bypass the thermal shield and control the driver
- The thermal shield works in conjunction with the control system to ensure that overheating will not harm the LEDs
- The wiring harness is connected with the use of the Purple lead as the positive (+) and the Grey lead as the negative (-) to an available control signal (by others)
- SF for 120, 277 and 347 line volts
- DF for 208, 240 and 480 line volts
- High temperature fuse holders factory installed inside the fixture housing. Fuse is included

CERTIFICATIONS AND LISTINGS

- UL 1598 Standard for wet locations for Luminaires
- UL 8750 Standard for Safety for Light Emitting Diode (LED) Equipment for use in Lighting Products
- UL 924 Standard for Emergency Lighting and Power Equipment Listed
- CSA C22.2#250.0 Luminaires
- IP66 rated
- IK07 rated
- FCC Compliant - Compliance to Title 47 Part 15 Subpart B
- 50°C Ambient
- DLC® (DesignLights Consortium) Qualified, with some Premium Qualified configurations. Please refer to the DLC website for specific product qualifications at www.designlights.org

WARRANTY

- 5 year warranty

KEY DATA

KEY DATA	
Lumen Range	4189–13,860
Wattage Range	35–130
Efficacy Range (LPW)	82–125
Reported Life (Hours)	L70/60,000
Weight	19 lbs 8.6 kg

DATE:

LOCATION:

TYPE:

PROJECT:

CATALOG #:

ORDERING GUIDE

Example: PGL8-5C-128L-65-3K7-UNV-GTT-NXWS40F

CATALOG #

HOUSING

PGL8															
Housing		Distribution		LED Engine		Color Temp		Voltage		Color					
PGL8	Parking Garage Luminaire	5C	Type V Concentrated	<u>5C, 5Q & 5R Distributions Only</u>		27K8 ⁹	2700, 80 CRI	UNV	Universal 120–277V	BLS	Black Gloss Smooth	LGT	Light Grey Matte Textured		
		5Q	Type V Square	128L-35	4500 lm	3K7	3000K, 70 CRI			BLT	Black Matte Textured	PSS	Platinum Silver Gloss Smooth		
		5R	Type V Rectangular	128L-55	6000 lm	3K8	3000K, 80 CRI			347	347V	VGT	Verde Green Matte Textured		
		ASY	Asymmetric	128L-65	7500 lm	35K8 ⁹	3500K, 80 CR							480	480V
				128L-85	9500 lm	4K7	4000K, 70 CRI			GTT	Graphite Matte Textured	LGS	Light Grey Gloss Smooth		
				128L-110 ⁶	11500 lm	4K8	4000K, 80 CRI								
				128L-130 ⁶	13500 lm	5K7	5000K, 70 CRI			Consult factory for other CCTs and CRIs					
				<u>ASY Distribution Only</u>											
				64L-50	5000 lm										
				64L-70	6500 lm										
		64L-90	7500 lm												

Control Options		Options & Control Accessories	
<u>NX Networked Wireless</u>		SF	Single Fuse 120, 277, 347 Line Volts
NXW ⁴	NX Networked Wireless Radio Module NXRM2 and Bluetooth Programming, without Sensor	DF	Double Fuse 208, 240, 480 Line Volts
NXWS12F ⁴	NX Networked Wireless Enabled Integral NXSMP2-OMNI PIR Occupancy Sensor with Automatic Dimming Photocell and Bluetooth Programming	PB22 ⁷	Balanced Pendant J-Box and Bird Shroud
NXWS40F ⁴	NX Networked Wireless Enabled Integral NXSMP2-HMO PIR Occupancy Sensor with Automatic Dimming Photocell and Bluetooth Programming	PB21 ⁸	Balanced Pendant J-Box and Bird Shroud
<u>LightGRID+ Wireless</u>		WM	Wall Mount
WIR	LightGRID+ In-Fixture Module	NU	No Uplight
WIRSC	LightGRID+ Module and Occupancy Sensor	EM ⁵	Integral Battery Backup Unit (16Wh)
WIR924 ³	LightGRID+ In-Fixture Module with UL924 Dimming Bypass Module for Controls Override	SCPREMOTE	Remote control for SCP option. Order at least one per project to program and control the occupancy sensor
WIRSC924 ³	LightGRID+ Module and Occupancy Sensor with UL924 Dimming Bypass Module for Controls Override		
<u>Sensor Controls</u>			
SCP-8F ³	Remote Control Programmable Line Voltage Sensor (8–12' Recommended Mounting Height), use with SCPREMOTE		
SCP-20F ³	Remote Control Programmable Line Voltage Sensor (12–20' Recommended Mounting Height), use with SCPREMOTE		
SCP924-8F ³	Programmable Sensor with UL924 Dimming Bypass Module for Controls Override (8–12' Recommended Mounting Height)		
SCP924-20F ³	Programmable Sensor with UL924 Dimming Bypass Module for Controls Override (12–20' Recommended Mounting Height)		
OCM ³	Microwave Occupancy Module (8-12' Recommended Mounting Height)		

- Notes:
- 1

Consult factory for custom color, marine and corrosive finish options
- 2

Not available with EM and 480V
- 3

Not available with EM and 128L-110/130 and 480V
- 4

Not available with EM
- 5

Not available with all control options or 347/480V
- 6

Not available with EM or SCP options
- 7

PB22: 128L-35, 128L-55, 128L-65, 128L-85, 64L-50, 64L-70, 64L-90
- 8

PB21: 128L-110, 128L-130
- 9

Scaling factors 27K8 = 0.859, 35K8 = 0.906 of 5K7 lumen packages

CONTROLS

NX Lighting Controls:
Supports both indoor and outdoor applications in a variety of deployment options- wired, wireless, hybrid.
Integrates with and enables a wide array of luminaires.




NX Integrated Controls Reference								
NX OPTION	Sensor	Networkable	Scheduling	Occupancy	Daylight Harvesting	0–10V Dimming	On/off Control	Bluetooth® App Programming
NX Networked Wireless								
NXW	N/A	Yes	Yes	No	No	Yes	Yes	Yes
NXWS12F	NXSMP2-OMNI	Yes	Yes	Yes	Yes	Yes	Yes	Yes
NXWS40F	NXSMP2-HMO	Yes	Yes	Yes	Yes	Yes	Yes	Yes

LightGRID+:
Supports remote management, monitoring and metering of outdoor wireless lighting applications such as smart campuses, smart cities, parking lots, parking lots and roadways.




LightGRID+ Reference									
LightGRID+ Option	Sensor	Networkable	Scheduling	Occupancy	Daylight Harvesting	0–10V Dimming	On/off Control	Programming	Commissioning
Networked – Wireless									
WIR	WIR-RMI-IO	Yes	Yes	No	Yes	Yes	Yes	LightGRID+ Gateway	On-site
WIRSC	WIR-RMI-IO with Motion Sensor	Yes	Yes	Yes	Yes	Yes	Yes	LightGRID+ Gateway	On-site




DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

CONTROLS CONTINUED

NXWS12F:



NXWS40F:



DATE:

LOCATION:

TYPE:

PROJECT:

CATALOG #:


DELIVERED LUMENS

LEDS #	NOMINAL WATTS	NOMINAL LUMENS	DISTRIBUTION	3000K 70CRI					4000K 70CRI					5000K 70CRI				
				LUMEN	B	U	G	LM/W	LUMEN	B	U	G	LM/W	LUMEN	B	U	G	LM/W
64L	50	4500	ASY	4811	1	3	3	95.6	4890	1	3	3	97.2	4920	1	3	3	97.8
	70	6000	ASY	6285	2	3	3	91.5	6389	2	3	3	93.0	6428	2	3	3	93.6
	90	7500	ASY	7278	2	3	3	82.2	7398	2	3	3	83.5	7443	2	3	3	84.0
128L	35	4500	5Q	4359	2	3	2	116.5	4431	2	3	2	120.2	4458	2	3	2	118.1
			5R	4189	2	3	2	111.9	4258	2	3	2	113.7	4284	2	3	2	113.4
			5C	4588	2	3	1	122.6	4664	2	3	1	124.6	4692	2	3	1	125.6
	55	6000	5Q	6097	3	3	3	113.8	6197	3	3	3	115.7	6235	3	3	3	116.4
			5R	5985	2	3	2	111.8	6084	2	3	2	113.6	6121	2	3	2	114.3
			5C	6432	2	3	1	120.1	6538	2	3	1	122.1	6578	2	3	1	122.8
	65	7500	5Q	7526	3	3	3	114.8	7650	3	3	3	116.7	7697	3	3	3	117.4
			5R	7389	3	3	2	112.7	7511	3	3	2	114.5	7556	3	3	2	115.2
			5C	7940	2	3	1	121.1	8071	2	3	2	123.1	8120	2	3	2	123.8
	85	9500	5Q	9360	3	3	3	110.7	9515	3	3	3	112.5	9573	3	3	3	113.2
			5R	9189	3	3	3	108.7	9341	3	3	3	110.5	9398	3	3	3	111.1
			5C	9875	3	3	2	116.8	10038	3	3	2	118.7	10099	3	3	2	119.4
	110	11500	5Q	11264	3	3	3	101.0	11450	3	3	3	102.6	11520	3	3	3	103.3
			5R	11058	3	3	3	99.1	11241	3	3	3	100.8	11310	3	3	3	101.4
			5C	11883	3	3	2	106.5	12079	3	3	2	108.3	12153	3	3	2	108.9
	130	13500	5Q	12846	3	3	4	97.4	13058	3	3	4	99.0	13138	4	3	4	99.5
			5R	12612	3	3	3	95.6	12820	3	3	3	97.2	12898	3	3	3	97.8
			5C	13552	3	3	2	102.7	13776	3	3	2	104.4	13860	3	3	2	105.1


CRI LUMEN MULTIPLIER	
CCT	80 CRI
3000K	0.9408
4000K	0.9067

DIMENSIONS


STANDARD: 19 lbs 8.6 kg




BIRD SHROUD




WALL MOUNT: 20 lbs 9.07 kg



BOTTOM VIEW



FRONT VIEW
EPA: 0.47



SIDE VIEW
EPA: 0.64

PHOTOMETRY

PGL8-5C-128L-65-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	8071
Watts	65.6
Efficacy	123.0
IES Type	VS
BUG Rating	B2-U3-G2
Mounting Height	10 ft
Grid Scale	10 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	3920.50	49%
Downward House Side	3920.51	49%
Downward Total	7841.01	97%
Upward Street Side	115.73	1%
Upward House Side	115.73	1%
Upward Total	231.46	3%
Total Flux	8072	100%

ISOFOOT CANDLE PLOT



PGL8-5Q-128L-65-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	7650
Watts	65.58
Efficacy	116.7
IES Type	VS
BUG Rating	B3-U3-G3
Mounting Height	10 ft
Grid Scale	10 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	3678.58	48%
Downward House Side	3678.59	48%
Downward Total	7357.17	96%
Upward Street Side	146.68	2%
Upward House Side	146.68	2%
Upward Total	293.36	4%
Total Flux	7651	100%

ISOFOOT CANDLE PLOT



PHOTOMETRY CONTINUED

PGL8-5R-128L-65-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	7511
Watts	65.6
Efficacy	114.5
IES Type	VS
BUG Rating	B3-U3-G2
Mounting Height	10 ft
Grid Scale	10 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
Downward Street Side	3628.24	48%
Downward House Side	3628.25	48%
Downward Total	7256.49	97%
Upward Street Side	127.68	2%
Upward House Side	127.68	2%
Upward Total	255.36	3%
Total Flux	7512	100%

ISOFOOT CANDLE PLOT



PGL8-ASY-64L-90-4K7


LUMINAIRE DATA

Description	4000 Kelvin, 70CRI
Delivered Lumens	7398
Watts	88.59
Efficacy	83.5
IES Type	IV
BUG Rating	B2-U3-G3
Mounting Height	10 ft
Grid Scale	10 ft

ZONAL LUMEN SUMMARY


Zone	Lumens	% Luminaire
Downward Street Side	4817.00	65%
Downward House Side	2293.42	31%
Downward Total	7110.42	96%
Upward Street Side	147.77	2%
Upward House Side	140.83	2%
Upward Total	288.60	4%
Total Flux	7399	100%

ISOFOOT CANDLE PLOT



TM-30 DATA

COLOR VECTOR GRAPHIC




— Reference Illuminant — Test Source

TEST SOURCE

R _f	72
R _g	93
CCT(K)	3982
D _{uv}	0.0014
x	0.3822
y	0.3808
CIE R _a	73

SPECTRAL POWER DISTRIBUTION COMPARISON




ELECTRICAL DATA

ELECTRICAL												DIMMING					
LIGHT ENGINE	SYSTEM WATTS	DRIVE CURRENT	LINE VOLTAGE		AMPS AC						MIN. POWER FACTOR	MAX THD (%)	DIMMING RANGE	SOURCE CURRENT OUT OF 0-10V		ABSOLUTE VOLTAGE RANGE ON 0-10V (+)	
			VAC	HZ	120	208	240	277	347	480				MIN	MAX	MIN	MAX
64L	50.3	450 mA	120-480	50/60	0.42	0.24	0.21	0.18	0.15	0.10	>0.9	20	10% to 100%	0mA	1mA	0V	10V
	68.7	610 mA			0.57	0.33	0.29	0.25	0.20	0.14							
	88.6	780 mA			0.74	0.43	0.37	0.32	0.26	0.18							
128L	37.4	350 mA			0.31	0.18	0.16	0.14	0.11	0.08							
	53.6	500 mA			0.45	0.26	0.22	0.19	0.15	0.11							
	65.6	625 mA			0.55	0.32	0.27	0.24	0.19	0.14							
	84.6	800 mA			0.70	0.41	0.35	0.31	0.24	0.18							
	111.6	510 mA			0.93	0.54	0.46	0.40	0.32	0.23							
131.9	600 mA	1.10			0.63	0.55	0.48	0.38	0.27								

TM-21 LIFETIME CALCULATION - PROJECTED LUMEN MAINTENANCE (25°C / 77°C)						
HOURS	0	25,000	36,000	50,000	100,000	REPORTED L70
Projected Lumen Maintenance	100%	94.0%	91.9%	89.3%	80.6%	> 60,000

ADDITIONAL INFORMATION


LENS



5Q: Type V Square
ASY: Asymmetric



5C: Type V Concentrated



5R: Type V Rectangular

DATE:	LOCATION:
TYPE:	PROJECT:
CATALOG #:	

ADDITIONAL INFORMATION CONTINUED

CONTROL OPTIONS SENSORS



Occupancy Sensor (NX & SCP)

Options



Balanced Pendant J-Box and Bird Shroud (64L and 128L)



Arm Mount