

PURSUIT

FEATURES

- Sections can be joined for runs up to 150' with seamless lens
- Electrical Connections IP68 rated
- Symmetric, Asymmetric, Wall Graze & Wall Wash Distributions
- "L", "T" & "X" Illuminated connectors for custom shapes
- Output up to 1,000 lm/ft in each direction
- Fixed arm, adjustable arm, pendant, wall & mullion mounting options



ORDERING GUIDE

Example: RNLTX-L-ID-5-3K8-DL-UNV-BLT

CATALOG #


HOUSING

RNLTX												
Housing	Light Engine	Lumen Output		CCT/CRI		Shielding		Voltage		Finish		
RNLTX-L Pursuit L shape illuminated connector	D	Direct (Down)	5	500 lumens/ft	3K8	3000K, 80 CRI	DL	Diffuse lens - Down Only	UNV	120-277V	BLS	Black Gloss Smooth
	ID ¹	Bidirectional (Up & Down Light)	7	750 lumens/ft	3K9	3000K, 90 CRI	CL	Clear lens		BLT	Black Matte Textured	
RNLTX-T Pursuit T shape illuminated connector	I ¹	Indirect (Up Light)	10	1000 lumens/ft	35K8	3500K, 80 CRI					DBS	Dark Bronze Gloss Smooth
					4K8	4000K, 80 CRI					DBT	Dark Bronze Matte Textured
RNLTX-X Pursuit X shape illuminated connector					4K9	4000K, 90 CRI					GTT	Graphite Matte Textured
					5K8	5000K, 80 CRI					LGS	Light Grey Gloss Smooth
											LGT	Light Grey Matte Textured
											PSS	Platinum Silver Gloss Smooth
											VGT	Verde Green Matte Textured
											WHS	White Gloss Smooth
											WHT	White Matte Textured
											Color Option	
											CC ²	Custom Color


ACCESSORIES

Illuminated Connectors
(Enables Custom Shapes)

- RNLTX-L L shape
- RNLTX-T T shape
- RNLTX-XX shape



Connectors for the RND, Bidirectional (Up and Down) and RNI (Up)



Connectors for the RND, Direct (Down)

¹ The top of the connectors are not lit. Both sides connects are not lit for the up configuration.

² Consult factory for custom color, marine and corrosive finish options.