






# Photocontrols

## ORDERING INFORMATION

	Catalog Number	Voltage	Max. Watts Incandescent		Max. Watts HID		Weight	
					HPF	NPF	lbs	kg
<b>PHOTOCONTROL – BUTTON TYPE<sup>1</sup></b>								
	<b>PBT-1<sup>6</sup></b>	120	1200		400	250	.125	0.1
	<b>PBT-234<sup>6</sup></b>	208/240/277	1200		400	250	.125	0.1
<b>PHOTOCONTROL – 1/2" THREAD MOUNT<sup>2</sup></b>								
	<b>PTA-1<sup>6</sup></b>	120	2000		1000	400	.25	0.1
	<b>PTA-8<sup>6</sup></b>	120-277	2000		1000	400	.25	0.1
	<b>PTA-5</b>	480	2000		1000	400	.25	0.1
<b>PHOTOCONTROL – TWIST-LOCK® CELL<sup>3</sup></b>								
	<b>PTL-1<sup>6</sup></b>	120	1800		1000	400	.25	0.1
	<b>PTL-8<sup>6</sup></b>	120-277	1800		1000	400	.25	0.1
	<b>PTL-5</b>	480	1800		1000	400	.25	0.1
<b>RECEPTACLE – REMOTE TWIST-LOCK® CELL WITH BRACKET<sup>4</sup></b>								
	<b>PRR</b>	120-480	1800		1000	400	.5	0.2
<b>SHORTING CAP – TWIST-LOCK® MOUNT<sup>5</sup></b>								
	<b>PSC</b>	Completes circuit – eliminates PCR					.25	0.1

<sup>1</sup> Miniature photocontrol sealed in a sturdy plastic housing 2 1/16" x 1 1/8" s 7/8" with 3/4" nipple length. Nipple dia. is 3/8" pipe thread – 5/8" outside diameter fits 1/2" tapped hubs Use in any suitable enclosed box or luminaire. A gasket and lock nut provide weather tight seal at exit point.

<sup>2</sup> Weatherproof photocontrol in a polycarbonate housing with field adjustable light sensitivity level feature. 3 5/8" x 2" x 1 1/2" housing with 5/8" nipple length.

<sup>3</sup> Weatherproof Twist-Lock® photocell enclosed in a high butyrate protective housing. Meets EEL-NEMA standards. For use with Twist-Lock® receptacles (PCR).

<sup>4</sup> Remote receptacle for PTL Twist-Lock® cell. Includes aluminum angle bracket and color coded leads. Bolts to wood poles, crossarms, walls or any flat surface.

<sup>5</sup> Weatherproof shorting cap to complete circuit and allow fixture to operate when Twist-Lock® photocontrol (PTL) is not used. For use with Twist-Lock® receptacles (PCR).

<sup>6</sup> CSA certified.